



MAXIBRASS CABLE GLANDS 2901 PG

Extended thread, Pg thread



CERTIFICATES 

 UL 514B  UL 514B

MAXIBRASS CABLE GLANDS 2901 PG

Technical characteristics

Material (Body)	Nickel plated brass
Material (Sealing ring)	Neoprene®
Material (Cable grip insert)	Polyamide PA6.6
Material (O-Ring)	Nitrile 70 sh A
Max operating temperature range	100 °C
Min operating temperature range	-25 °C



MAXIBRASS CABLE GLANDS 2901 PG

List of products

2901 Pg										
Type	P	Fixing hole diameter	ØA Min	ØA Max	B	E	C	L Min	L Max	Pack qty
2901.07N	Pg7	12.7 mm	3 mm	7 mm	16 mm	18 mm	12 mm	17 mm	20 mm	100
2901.09N	Pg9	15.5 mm	4 mm	8 mm	17 mm	19 mm	12 mm	16 mm	23 mm	100
2901.11N	Pg11	18.8 mm	4.5 mm	10 mm	20 mm	23 mm	12 mm	20 mm	25 mm	100
2901.13N	Pg13,5	20.5 mm	5 mm	12 mm	22 mm	25 mm	12 mm	20 mm	26 mm	50
2901.16N	Pg16	22.6 mm	7 mm	13 mm	24 mm	27 mm	12 mm	20 mm	27 mm	50
2901.21N	Pg21	28.5 mm	10 mm	17 mm	30 mm	33 mm	12 mm	24 mm	30 mm	50
2901.29N	Pg29	37.2 mm	17 mm	25 mm	40 mm	45 mm	15 mm	30 mm	37 mm	25
2901.36N	Pg36	47.2 mm	20 mm	32 mm	50 mm	55 mm	15 mm	38 mm	48 mm	10
2901.42N	Pg42	54.2 mm	28 mm	38 mm	57 mm	63 mm	15 mm	39 mm	48 mm	5