



## MAXIBRASS CABLE GLANDS 2911 PG

*Extended thread and reduced cable entry, Pg thread*



CERTIFICATES 

 UL 514B  UL 514B

# MAXIBRASS CABLE GLANDS 2911 PG

## *Technical characteristics*


Material (Body)	Nickel plated brass
Material (Sealing ring)	Neoprene®
Material (Cable grip insert)	Polyamide PA6.6
Material (O-Ring)	Nitrile 70 sh A
Max operating temperature range	100 °C
Min operating temperature range	-25 °C



# MAXIBRASS CABLE GLANDS 2911 PG

## List of products

### 2911 Pg



Type	P	Fixing hole diameter	ØA Min	ØA Max	B	E	C	L Min	L Max	Pack qty
2911.07N	Pg7	12.7 mm	1 mm	5 mm	16 mm	18 mm	12 mm	16 mm	20 mm	100
2911.09N	Pg9	15.5 mm	2 mm	6 mm	17 mm	19 mm	12 mm	17 mm	23 mm	100
2911.11N	Pg11	18.8 mm	2.5 mm	7 mm	20 mm	23 mm	12 mm	20 mm	25 mm	100
2911.13N	Pg13,5	20.5 mm	4 mm	10 mm	22 mm	25 mm	12 mm	20 mm	26 mm	50
2911.16N	Pg16	22.6 mm	5 mm	10 mm	24 mm	27 mm	12 mm	20 mm	27 mm	100
2911.21N	Pg21	28.5 mm	6 mm	13 mm	30 mm	33 mm	12 mm	24 mm	30 mm	50
2911.29N	Pg29	37.2 mm	11 mm	20 mm	40 mm	45 mm	15 mm	30 mm	37 mm	25
2911.36N	Pg36	47.2 mm	18 mm	26 mm	50 mm	55 mm	15 mm	38 mm	48 mm	10
2911.42N	Pg42	54.2 mm	24 mm	31 mm	57 mm	63 mm	15 mm	39 mm	48 mm	5