

MAXIINOX CABLE GLANDS 7900

Stainless Steel 303 (X8 CrNiS 18-9)



CERTIFICATES 

 BT 2006/95/CE

MAXIINOX CABLE GLANDS 7900

Technical characteristics


Material (Body)	Stainless steel AISI 303
Material (Sealing ring)	Neoprene®
Material (Cable grip insert)	Polyamide PA6.6
Material (O-Ring)	Nitrile 70 sh A



MAXIINOX CABLE GLANDS 7900

List of products

7900 M



Type	P	Fixing hole diameter	ØA Min	ØA Max	B	E	C	L Min	L Max	Pack qty	Min. pack qty
7900.M12	M12X1,5	12.2 mm	3 mm	7 mm	16 mm	18 mm	6.5 mm	16 mm	20 mm	90	30
7900.M16	M16X1,5	16.2 mm	4.5 mm	10 mm	20 mm	23 mm	7 mm	20 mm	25 mm	120	30
7900.M20	M20X1,5	20.5 mm	7 mm	13 mm	24 mm	27 mm	8 mm	20 mm	27 mm	75	25
7900.M25	M25X1,5	25.4 mm	10 mm	17 mm	29 mm	32 mm	8 mm	24 mm	30 mm	40	20
7900.M32	M32X1,5	32.5 mm	11 mm	21 mm	36 mm	40 mm	9 mm	27 mm	34 mm	15	
7900.M40	M40X1,5	40.5 mm	19 mm	28 mm	45 mm	50 mm	9 mm	34 mm	42 mm	15	
7900.M50	M50X1,5	50.5 mm	26 mm	35 mm	54 mm	60 mm	10 mm	35 mm	43 mm	10	
7900.M63	M63X1,5	64 mm	34 mm	45 mm	67 mm	74 mm	15 mm	40 mm	52 mm	5	

7900 Pg


Type	P	Fixing hole diameter	ØA Min	ØA Max	B	E	C	L Min	L Max	Pack qty	Min. pack qty
7900.07	Pg7	12.7 mm	3 mm	7 mm	16 mm	18 mm	5 mm	20 mm	16 mm	90	30
7900.09	Pg9	15.5 mm	4 mm	8 mm	17 mm	19 mm	6 mm	23 mm	17 mm	90	30
7900.11	Pg11	18.8 mm	4.5 mm	10 mm	20 mm	23 mm	6 mm	25 mm	20 mm	60	30
7900.13	Pg13,5	20.5 mm	5 mm	12 mm	22 mm	25 mm	6.5 mm	26 mm	20 mm	90	30
7900.16	Pg16	22.6 mm	7 mm	13 mm	24 mm	27 mm	6.5 mm	27 mm	20 mm	60	30
7900.21	Pg21	28.5 mm	10 mm	17 mm	30 mm	33 mm	7 mm	30 mm	24 mm	40	20
7900.29	Pg29	37.2 mm	17 mm	25 mm	40 mm	45 mm	8 mm	37 mm	3 mm	30	15
7900.36	Pg36	47.2 mm	20 mm	32 mm	50 mm	55 mm	8 mm	48 mm	38 mm	10	
7900.42	Pg42	54.2 mm	28 mm	38 mm	57 mm	63 mm	10 mm	46 mm	36 mm	5	
7900.48	Pg48	60 mm	34 mm	45 mm	67 mm	74 mm	15 mm	52 mm	40 mm	5	