

MAXIINOX CABLE GLANDS 7900A

Stainless Steel 316L (X2 CrNiMo 17-12-2)



CERTIFICATES 

 BT 2006/95/CE

MAXIINOX CABLE GLANDS 7900A

Technical characteristics


Material (Body)	Stainless steel AISI 316L
Material (Sealing ring)	Neoprene®
Material (Cable grip insert)	Polyamide PA6.6
Material (O-Ring)	Nitrile 70 sh A



MAXIINOX CABLE GLANDS 7900A

List of products

7900A M



Type	P	Fixing hole diameter	ØA Min	ØA Max	B	E	C	L Min	L Max	Pack qty	Min. pack qty
7900A.M12	M12X1,5	12.2 mm	3 mm	7 mm	16 mm	18 mm	6.5 mm	16 mm	20 mm	60	20
7900A.M16	M16X1,5	16.2 mm	4.5 mm	10 mm	20 mm	23 mm	7 mm	20 mm	25 mm	80	20
7900A.M20	M20X1,5	20.5 mm	7 mm	13 mm	24 mm	27 mm	8 mm	20 mm	27 mm	60	20
7900A.M25	M25X1,5	25.4 mm	10 mm	17 mm	29 mm	32 mm	8 mm	24 mm	30 mm	30	15
7900A.M32	M32X1,5	32.5 mm	11 mm	21 mm	36 mm	40 mm	9 mm	27 mm	34 mm	12	
7900A.M40	M40X1,5	40.5 mm	19 mm	28 mm	45 mm	50 mm	9 mm	34 mm	42 mm	10	
7900A.M50	M50X1,5	50.5 mm	26 mm	35 mm	54 mm	60 mm	10 mm	35 mm	43 mm	7	
7900A.M63	M63X1,5	64 mm	34 mm	45 mm	67 mm	74 mm	15 mm	40 mm	52 mm	5	

7900A Pg



Type	P	Fixing hole diameter	ØA Min	ØA Max	B	E	C	L Min	L Max	Pack qty	Min. pack qty
7900A.07	Pg7	12.7 mm	3 mm	7 mm	16 mm	18 mm	5 mm	16 mm	20 mm	60	20
7900A.09	Pg9	15.5 mm	4 mm	8 mm	17 mm	19 mm	6 mm	17 mm	23 mm	60	20
7900A.11	Pg11	18.8 mm	4.5 mm	10 mm	20 mm	23 mm	6 mm	20 mm	25 mm	100	20
7900A.13	Pg13,5	20.5 mm	5 mm	12 mm	22 mm	25 mm	6.5 mm	20 mm	26 mm	100	20
7900A.16	Pg16	22.6 mm	7 mm	13 mm	24 mm	27 mm	6.5 mm	20 mm	27 mm	40	20
7900A.21	Pg21	28.5 mm	10 mm	17 mm	30 mm	33 mm	7 mm	24 mm	30 mm	60	15
7900A.29	Pg29	37.2 mm	17 mm	25 mm	40 mm	45 mm	8 mm	30 mm	37 mm	20	10
7900A.36	Pg36	47.2 mm	20 mm	32 mm	50 mm	55 mm	8 mm	38 mm	48 mm	7	
7900A.42	Pg42	54.2 mm	28 mm	38 mm	57 mm	63 mm	10 mm	36 mm	46 mm	5	
7900A.48	Pg48	60 mm	34 mm	45 mm	67 mm	74 mm	15 mm	40 mm	52 mm	5	