

HALOGEN FREE INSULATED TERMINALS P03-M



CERTIFICATES 

HALOGEN FREE INSULATED TERMINALS **P03-M**

Technical characteristics

Material (Body)	ETP Copper electrolytically tinned
Material (Partially reinforced)	Polycarbonate
Colour (Partially reinforced)	Red



HALOGEN FREE INSULATED TERMINALS P03-M

List of products

P03-M Cable type: copper, Minimum section: 0.25 mm², Maximum section: 1.5 mm²

Type	Ø Stud mm	Øi	B	M	N	L	d	Pack qty	Min. pack qty
P03-M3	3 mm	1.8 mm	6 mm	4.5 mm	3.5 mm	22 mm	3.2 mm	3,000	100
P03-M3.5	3.5 mm	1.8 mm	6.5 mm	4.5 mm	3.5 mm	22 mm	3.7 mm	3,000	100
P03-M4	4 mm	1.8 mm	6.5 mm	5 mm	4 mm	23 mm	4.3 mm	3,000	100
P03-M5	5 mm	1.8 mm	7.5 mm	5.5 mm	4.5 mm	24 mm	5.3 mm	3,000	100
P03-M6	6 mm	1.8 mm	9 mm	6 mm	5 mm	25 mm	6.4 mm	3,000	100

P03-M Cable type: flexible copper, Minimum section: 0.25 mm², Maximum section: 1.5 mm²

Type	Ø Stud mm	Øi	B	M	N	L	d	Pack qty	Min. pack qty
P03-M3	3 mm	1.8 mm	6 mm	4.5 mm	3.5 mm	22 mm	3.2 mm	3,000	100
P03-M3.5	3.5 mm	1.8 mm	6.5 mm	4.5 mm	3.5 mm	22 mm	3.7 mm	3,000	100
P03-M4	4 mm	1.8 mm	6.5 mm	5 mm	4 mm	23 mm	4.3 mm	3,000	100
P03-M5	5 mm	1.8 mm	7.5 mm	5.5 mm	4.5 mm	24 mm	5.3 mm	3,000	100
P03-M6	6 mm	1.8 mm	9 mm	6 mm	5 mm	25 mm	6.4 mm	3,000	100