

## HALOGEN FREE INSULATED TERMINALS P06-M



CERTIFICATES 

# HALOGEN FREE INSULATED TERMINALS P06-M

## *Technical characteristics*

Material (Body)	ETP Copper electrolytically tinned
Material (Partially reinforced)	Polycarbonate
Colour (Partially reinforced)	Blue



# HALOGEN FREE INSULATED TERMINALS P06-M

## List of products

### **P06-M** Cable type: copper, Minimum section: 1.5 mm<sup>2</sup>, Maximum section: 2.5 mm<sup>2</sup>

Type	Ø Stud mm	Øi	B	M	N	L	d	Pack qty	Min. pack qty
P06-M3	3 mm	2.4 mm	6 mm	4.5 mm	3.5 mm	22.6 mm	3.2 mm	3,000	100
P06-M3.5	3.5 mm	2.4 mm	6.5 mm	4.5 mm	3.5 mm	22.6 mm	3.7 mm	3,000	100
P06-M4	4 mm	2.4 mm	7.5 mm	5 mm	4 mm	23.6 mm	4.3 mm	3,000	100
P06-M5	5 mm	2.4 mm	8.5 mm	5.5 mm	4.5 mm	24.6 mm	5.3 mm	2,500	100
P06-M6	6 mm	2.4 mm	9 mm	6 mm	5 mm	25.6 mm	6.4 mm	2,000	100
P06-M8	8 mm	2.4 mm	12 mm	9 mm	8 mm	31.3 mm	8.4 mm	1,500	100
P06-M10	10 mm	2.4 mm	18 mm	14 mm	12 mm	43 mm	10.5 mm	1,000	100
P06-M12	10 mm	2.4 mm	19 mm	14 mm	12 mm	43 mm	13.2 mm	500	100

### **P06-M** Cable type: flexible copper, Minimum section: 1.5 mm<sup>2</sup>, Maximum section: 2.5 mm<sup>2</sup>

Type	Ø Stud mm	Øi	B	M	N	L	d	Pack qty	Min. pack qty
P06-M3	3 mm	2.4 mm	6 mm	4.5 mm	3.5 mm	22.6 mm	3.2 mm	3,000	100
P06-M3.5	3.5 mm	2.4 mm	6.5 mm	4.5 mm	3.5 mm	22.6 mm	3.7 mm	3,000	100
P06-M4	4 mm	2.4 mm	7.5 mm	5 mm	4 mm	23.6 mm	4.3 mm	3,000	100
P06-M5	5 mm	2.4 mm	8.5 mm	5.5 mm	4.5 mm	24.6 mm	5.3 mm	2,500	100
P06-M6	6 mm	2.4 mm	9 mm	6 mm	5 mm	25.6 mm	6.4 mm	2,000	100
P06-M8	8 mm	2.4 mm	12 mm	9 mm	8 mm	31.3 mm	8.4 mm	1,500	100
P06-M10	10 mm	2.4 mm	18 mm	14 mm	12 mm	43 mm	10.5 mm	1,000	100
P06-M12	10 mm	2.4 mm	19 mm	14 mm	12 mm	43 mm	13.2 mm	500	100