

HALOGEN FREE INSULATED TERMINALS P1-M



CERTIFICATES 

HALOGEN FREE INSULATED TERMINALS **P1-M**

Technical characteristics

Material (Body)	ETP Copper electrolytically tinned
Material (Partially reinforced)	Polycarbonate
Colour (Partially reinforced)	Yellow



HALOGEN FREE INSULATED TERMINALS P1-M

List of products

P1-M Cable type: copper, Minimum section: 4 mm ² , Maximum section: 6 mm ²									
Type	Ø Stud mm	Øi	B	M	N	L	d	Pack qty	Min. pack qty
P1-M3	3 mm	3.6 mm	7.5 mm	4.5 mm	3.5 mm	28 mm	3.2 mm	1,000	100
P1-M3.5	3.5 mm	3.6 mm	7.5 mm	4.5 mm	3.5 mm	28 mm	3.7 mm	1,000	100
P1-M4	4 mm	3.6 mm	8 mm	5 mm	4 mm	30 mm	4.3 mm	1,000	100
P1-M5	5 mm	3.6 mm	9 mm	6.5 mm	6 mm	32.3 mm	5.3 mm	1,000	100
P1-M6	6 mm	3.6 mm	11 mm	7 mm	6 mm	32.8 mm	6.4 mm	1,000	100
P1-M8	8 mm	3.6 mm	14 mm	9 mm	8 mm	36.8 mm	8.4 mm	1,000	100
P1-M10	10 mm	3.6 mm	16.5 mm	11 mm	10 mm	41.4 mm	10.5 mm	1,000	100

P1-M Cable type: flexible copper, Minimum section: 4 mm ² , Maximum section: 6 mm ²									
Type	Ø Stud mm	Øi	B	M	N	L	d	Pack qty	Min. pack qty
P1-M3	3 mm	3.6 mm	7.5 mm	4.5 mm	3.5 mm	28 mm	3.2 mm	1,000	100
P1-M3.5	3.5 mm	3.6 mm	7.5 mm	4.5 mm	3.5 mm	28 mm	3.7 mm	1,000	100
P1-M4	4 mm	3.6 mm	8 mm	5 mm	4 mm	30 mm	4.3 mm	1,000	100
P1-M5	5 mm	3.6 mm	9 mm	6.5 mm	6 mm	32.3 mm	5.3 mm	1,000	100
P1-M6	6 mm	3.6 mm	11 mm	7 mm	6 mm	32.8 mm	6.4 mm	1,000	100
P1-M8	8 mm	3.6 mm	14 mm	9 mm	8 mm	36.8 mm	8.4 mm	1,000	100
P1-M10	10 mm	3.6 mm	16.5 mm	11 mm	10 mm	41.4 mm	10.5 mm	1,000	100