

## SINGLE POLE TERMINAL BLOCKS Z6-3

*indirect clamping  
nominal section 6 sqmm*

3, 5, 6 and 10 way, single pole terminal blocks for conductor section 1 to 6 sqmm. Self contained and robust, for both industrial and domestic use. The indirect clamping of the "ZETApiù" terminal blocks guarantees a low and stable contact resistance. Indirect clamping eliminates damage to the conductor strands. The easy-entry receptacles also grant a fast and reliable insertion of the cable.



CERTIFICATES 



CEI EN 60998-1



EN 60998-1



EN 60998-2-1

1:1993



EN 60998-1:2004



EN 60998-2-



EN 60998-1:2004



EN 60998-2-1: 2004

# SINGLE POLE TERMINAL BLOCKS Z6-3

## *Technical characteristics*

### PROPERTIES

Height	27.5 mm
Width	23 mm
Length	23 mm
No. hole	3
Pack qty	30
Weight	15 g
Easy entry	yes
UL94 class	V0
IP protection	20
Halogen Free	yes
Impulse voltage	450 V
Max application temperature	85 °C
Material (Body)	Polycarbonate
Material (Clamps)	Electroplated galvanized steel
Material (Connection plate)	ETP Copper electrolytically tinned



## SINGLE POLE TERMINAL BLOCKS **Z6-3**