

# SINGLE POLE TERMINAL BLOCKS Z16-3D

*indirect clamping  
nominal section 16 sqmm*

3, 4, 5, 8 and 12 way, single pole terminal blocks. Ideal for use as an equipotential bonding connector for both industrial and domestic use.



CERTIFICATES 



CEI EN 60998-1



CEI 23-21



EN 60998-1



EN 60998-2-1

# SINGLE POLE TERMINAL BLOCKS Z16-3D

## *Technical characteristics*

### PROPERTIES

Height	44 mm
Width	38 mm
Length	50 mm
No. hole	3
Pack qty	15
Weight	55.5 g
Impulse voltage	450 V
Clamp for DIN	yes
Easy entry	yes
UL94 class	V0
IP protection	20
Halogen Free	yes
Impulse voltage	450 V
Max application temperature	85 °C
Material (Body)	Polycarbonate
Material (Clamps)	Electroplated galvanized steel
Material (Connection plate)	ETP Copper electrolytically tinned
Max application temperature	85 °C
UL94 class	V0
IP protection	20
Easy entry	yes
Material (Body)	Polycarbonate
Material (Clamps)	Electroplated galvanized steel
Material (Connection plate)	ETP Copper electrolytically tinned



## SINGLE POLE TERMINAL BLOCKS **Z16-3D**