

HYDRAULIC PRESSHEAD RHU230-630

general features

Hydraulic presshead complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max. Adaptor type AU230-130D is available as an optional extra enabling the head to utilise the semi-circular slotted dies which are common to most 130 kN tools. Also available is a series of dies for the compression of DIN electrical connectors, and a die for cutting copper, aluminium, aldreyl, aluminium-steel and steel conductors.



HYDRAULIC PRESSHEAD RHU230-630

Technical characteristics

PROPERTIES

Width	193 mm
Length	365 mm
Weight	9 kg
Nominal pressure	700 bar
Force developed	230 kN
Type of action	Crimp



HYDRAULIC PRESSHEAD RHU230-630

In the same kit

Storage

CASE VAL - Metallic carrying case VAL 230-630

Products used together

Tools

ELECTRICALLY DRIVEN HYDRAULIC PUMP CPE-1 - CPE-1

HYDRAULIC PUMPS B70M-P24 - B70M-P24

HYDRAULIC PUMPS CPP-0 - CPP-0

Electrically driven Hydraulic pump CPE-1-110 - CPE-1-110

HYDRAULIC PUMPS B70M-P24-CH - B70M-P24-CH

HYDRAULIC PUMPS PO7000 - PO7000

Through connectors

REDUCER THROUGH CONNECTORS MTMA--GC

MTMA400-240-GC	MTMA400-300-GC	MTMA500-300-GC
MTMA500-400-GC	MTMAD300-150-GC	MTMAD300-185-GC
MTMAD300-240-GC	MTMAD300-95-GC	

THROUGH CONNECTORS MTMA-GC

MTMA300-GC	MTMA500-GC
------------	------------

THROUGH CONNECTORS MTMA/1

MTMA400/1	MTMA500-40/1	MTMA630/1
-----------	--------------	-----------

Connectors

ALUMINIUM TERMINALS AA-M

AA300-M16	AA400-M16	AA500-40-M16
AA630-M16		

BIMETALLIC CONNECTORS CAA-M

CAA300-M16	CAA400-M16	CAA500-M16-TNBD
CAA630-4M8		

On request

Storage

CASE VAL - Metal carrying case VAL MAT 230-630