

HYDRAULIC CUTTING HEAD TC025

Max cutting diameter 25 mm

Hydraulic cutting head complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max. TC025 has the same cutting capability as HT-TC026.



CUTTING CAPACITY			
MATERIAL	TENSILE STRENGTH (daN/mm ²)	MAX CUTTING DIAMETER (mm)	
		HT-TC026	HT-TC026Y TC 025 B-TC026
ROPES & CONDUCTORS	COPPER	≤ 41	25
	ALUMINIUM	≤ 20	25
	ALDREY	≤ 34	25
	STEEL	≤ 180	INDICATIVE EXAMPLES: 7 x 3,0 : Ø est. = 9,0 mm 19 x 2,1 : Ø est. = 10,5 mm 19 x 2,3 : Ø est. = 11,5 mm
	MULTI STRANDS STEEL (STRANDS Qty ≥ 200)	≤ 180	18
	ACSR	≤ 180	25 INDICATIVE EXAMPLES: 26 x 2,50 + 7 x 1,95 : Ø est. = 15,85 26 x 3,06 + 7 x 2,38 : Ø est. = 19,38 26 x 3,60 + 7 x 2,80 : Ø est. = 22,80
RODS	STEEL	≤ 60	13
		≤ 42	16
	COPPER	≤ 30	20
		≤ 25	23

	ALUMINIUM	≤ 16	25
--	-----------	-----------	----

HYDRAULIC CUTTING HEAD TC025

Technical characteristics

PROPERTIES

Width	82 mm
Length	213 mm
Weight	2 kg
Nominal pressure	700 bar
Maximum cutting diameter	25 mm
Type of action	Cutting



HYDRAULIC CUTTING HEAD TC025

In the same kit

Storage

CASE VAL - Canvas bag 007

Products used together

Tools

18V Battery pump B1300PL - B1300PL

Electrically driven Hydraulic pump CPE-1-110 - CPE-1-110

HYDRAULIC PUMPS B70M-P24-CH - B70M-P24-CH

HYDRAULIC PUMPS PO7000 - PO7000

ELECTRICALLY DRIVEN HYDRAULIC PUMP CPE-1 - CPE-1

HYDRAULIC PUMPS B70M-P24 - B70M-P24

HYDRAULIC PUMPS CPP-0 - CPP-0