

ELECTRICALLY DRIVEN HYDRAULIC PUMP CPE-1

Electrically driven hydraulic pump, powered by a 230V / 50-60Hz singlephase electric motor.

The remote hand controller allows advancement and pressure release on completion of the crimping operation.

The mechanically actuated emergency button located on the pump body allows the pressure release at any time in case of power shortage.

It is equipped with:

- > high pressure flexible hose with female automatic quick coupler
- > remote hand controller
- > external supply connection cable



ELECTRICALLY DRIVEN HYDRAULIC PUMP **CPE-1**

Technical characteristics

PROPERTIES

Nominal pressure	700 bar
Motor voltage	230 V
Motor frequency	60 Hz
Length	372 mm
Width	223 mm
Height	482 mm
Weight	21 kg



ELECTRICALLY DRIVEN HYDRAULIC PUMP **CPE-1**

In the same kit

Tools

- Flexible hoses TF300-0

Quick couplers Q38

Q38-F

Q38-MS

On request

Accessories

- Transportation trolley CS-CPE-1

RCP-B70 - Remote foot controller RCP-B70

ERCH-WH - Control handle for flex hoses ERCH-WH

Products used together

Tools	
Hydraulic Crimping Head 130 kN RHC131LN-KV - Hydraulic Crimping Head 130 kN RHC131LN-KV	
HYDRAULIC CUTTING HEAD TC050 - TC050	
HYDRAULIC CUTTING HEAD TC055 - TC055	
HYDRAULIC CUTTING HEAD TC096 - TC096	
HYDRAULIC CUTTING HEAD TC120 - TC120	
HYDRAULIC PRESSHEAD RH50 - RH50	
HYDRAULIC PRESSHEAD RHM50 - RHM50	
HYDRAULIC PRESSHEAD RHU230-630 - RHU230-630	
HYDRAULIC PRESSHEAD RHU600 - RHU600	
HYDRAULIC PRESSHEADS RHM132 - RHM132	
Puller-type hole punching head RH-FL75 - RH-FL75	
HYDRAULIC CUTTING HEAD TC025 - TC025	
HYDRAULIC CUTTING HEAD TC050Y - TC050Y	
HYDRAULIC CUTTING HEAD TC085 - TC085	
HYDRAULIC CUTTING HEAD TC096-KV - TC096-KV	
HYDRAULIC PRESSHEAD ECW-H3D - ECW-H3D	
HYDRAULIC PRESSHEAD RHC131LN - RHC131LN	
HYDRAULIC PRESSHEAD RHU131-C - RHU131-C	
HYDRAULIC PRESSHEAD RHU520 - RHU520	
HYDRAULIC PRESSHEADS RHC131 - RHC131	
Piercing heads RHT	
RHT160	RHT160-60N
SPECIAL TOOLS Frame-type hole punching head RH-FC48N - RH-FC48N	