

ELECTRICALLY DRIVEN HYDRAULIC PUMP CPE-1-110

Electrically driven hydraulic pump, powered by a 110-115V / 50-60Hz singlephase electric motor.

Both models are IP 55 rated.

The remote hand controller allows advancement and pressure release on completion of the crimping operation.

The mechanically actuated emergency button located on the pump body allows the pressure release at any time in case of power shortage.

It is equipped with:

high pressure flexible hose with female automatic quick coupler

remote hand controller

external supply connection cable



ELECTRICALLY DRIVEN HYDRAULIC PUMP **CPE-1-110**

Technical characteristics

PROPERTIES

Height	482 mm
Width	223 mm
Length	372 mm
Weight	21 kg
Nominal pressure	700 bar
Motor voltage	115 V
Motor frequency	60 Hz



ELECTRICALLY DRIVEN HYDRAULIC PUMP **CPE-1-110**

In the same kit

Tools

- Flexible hoses TF300-0

Quick couplers Q38

Q38-F

Q38-MS

On request

Accessories

- Transportation trolley CS-CPE-1

RCP-B70 - Remote foot controller RCP-B70

ERCH-WH - Control handle for flex hoses ERCH-WH

Products used together

Tools

HYDRAULIC CUTTING HEAD TC025 - TC025

HYDRAULIC CUTTING HEAD TC050Y - TC050Y

HYDRAULIC CUTTING HEAD TC085 - TC085

HYDRAULIC CUTTING HEAD TC096-KV - TC096-KV

Hydraulic nut splitting tools RHTD

RHTD3241 Single blade head RHTD1724

HYDRAULIC PRESSHEAD RH50 - RH50

HYDRAULIC PRESSHEAD RHM50 - RHM50

HYDRAULIC PRESSHEAD RHU230-630 - RHU230-630

HYDRAULIC PRESSHEAD RHU600 - RHU600

HYDRAULIC PRESSHEADS RHM132 - RHM132

Puller-type hole punching head RH-FL75 - RH-FL75

HYDRAULIC CUTTING HEAD TC050 - TC050

HYDRAULIC CUTTING HEAD TC055 - TC055

HYDRAULIC CUTTING HEAD TC096 - TC096

HYDRAULIC CUTTING HEAD TC120 - TC120

HYDRAULIC PRESSHEAD ECW-H3D - ECW-H3D

HYDRAULIC PRESSHEAD RHC131LN - RHC131LN

HYDRAULIC PRESSHEAD RHU131-C - RHU131-C

HYDRAULIC PRESSHEAD RHU520 - RHU520

HYDRAULIC PRESSHEADS RHC131 - RHC131

Piercing heads RHT

RHT160 RHT160-60N

SPECIAL TOOLS

**Frame-type hole
punching head
RH-FC48N - RH-FC48N**