

HYDRAULIC PUMPS B70M-P24-CH

Portable electro-hydraulic pump, operating at 24V dc by battery for independent use, developing 700 bar pressure; it features an integral socket for connection to an external 24 V dc supply. It is also available insulated and operated by remote pneumatic hand controller and supplied with a nonconductive hose.



HYDRAULIC PUMPS B70M-P24-CH

Technical characteristics

PROPERTIES

Height	323 mm
Width	163 mm
Length	390 mm
Weight	9.2 kg
Nominal pressure	700 bar
Battery voltage	24 V
Battery current	0.13 Ah



HYDRAULIC PUMPS B70M-P24-CH

In the same kit

Accessories

External battery charger DC24 NiMH Battery 24V 3.1Ah BH2433 Shoulder strap 6000354

ERCH-WH - Control handle for flex hoses ERCH-WH

Storage

CASE VAL - Canvas bag 009

Products used together

Tools	
HYDRAULIC CUTTING HEAD TC025 - TC025	
HYDRAULIC CUTTING HEAD TC050Y - TC050Y	
HYDRAULIC CUTTING HEAD TC085 - TC085	
HYDRAULIC CUTTING HEAD TC096-KV - TC096-KV	
Hydraulic nut splitting tools RHTD	
RHTD3241	Single blade head RHTD1724
HYDRAULIC PRESSHEAD RH50 - RH50	
HYDRAULIC PRESSHEAD RHM50 - RHM50	
HYDRAULIC PRESSHEAD RHU230-630 - RHU230-630	
HYDRAULIC PRESSHEAD RHU600 - RHU600	
HYDRAULIC PRESSHEADS RHM132 - RHM132	
PRESSURE TEST DEVICE FOR HYDRAULIC PUMPS AND TOOLS MPC1 - MPC1	
SPECIAL TOOLS	
Frame-type hole punching head	
RH-FC48N - RH-FC48N	
HYDRAULIC CUTTING HEAD TC050 - TC050	
HYDRAULIC CUTTING HEAD TC055 - TC055	
HYDRAULIC CUTTING HEAD TC096 - TC096	
HYDRAULIC CUTTING HEAD TC120 - TC120	
HYDRAULIC PRESSHEAD ECW-H3D - ECW-H3D	
HYDRAULIC PRESSHEAD RHC131LN - RHC131LN	
HYDRAULIC PRESSHEAD RHU131-C - RHU131-C	
HYDRAULIC PRESSHEAD RHU520 - RHU520	
HYDRAULIC PRESSHEADS RHC131 - RHC131	
Piercing heads RHT	
RHT160	RHT160-60N
Puller-type hole punching head RH-FL75 - RH-FL75	