

## HYDRAULIC PRESSHEAD RHU450

*crimping force 450 kN*

Hydraulic presshead complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max. Adaptor type AU 450 130 D is available as an optional extra enabling the head to utilise the semi-circular slotted dies which are common to most 130 kN tools.



# HYDRAULIC PRESSHEAD RHU450

## *Technical characteristics*

### PROPERTIES

Width	120 mm
Length	260 mm
Weight	10.3 kg
Nominal pressure	700 bar
Force developed	450 kN
Type of action	Crimp



# HYDRAULIC PRESSHEAD RHU450

## *Products used together*

### Connectors

#### **COPPER TUBE CRIMPING LUGS ACCORDING TO DIN 46235 DR**

DR10-10	DR10-5	DR10-6
DR10-8	DR120-10	DR120-12
DR120-16	DR120-20	DR120-8
DR150-10	DR150-12	DR150-16
DR150-20	DR16-10	DR16-12
DR16-5	DR16-6	DR16-8
DR185-10	DR185-12	DR185-16
DR185-20	DR240-10	DR240-12
DR240-16	DR240-20	DR25-10
DR25-12	DR25-6	DR25-8
DR300-12	DR300-16	DR300-20
DR35-10	DR35-12	DR35-16
DR35-6	DR35-8	DR400-12
DR400-16	DR400-20	DR500-12
DR500-16	DR500-20	DR50-10
DR50-12	DR50-16	DR50-6
DR50-8	DR625-20	DR70-10
DR70-12	DR70-16	DR70-20
DR70-8	DR95-10	DR95-12
DR95-16	DR95-20	DR95-8

### Through connectors

#### **CRIMPING THROUGH CONNECTORS ACCORDING TO DIN 46267 T.1 DSV**

DSV10	DSV120	DSV150
DSV16	DSV185	DSV240
DSV25	DSV300	DSV35
DSV400	DSV50	DSV500
DSV6	DSV625	DSV70
DSV95		

## *In the same kit*

### Storage

#### **CASE VAL - Metallic case storage VAL 450**