

## HYDRAULIC CUTTING HEAD TC04N

Hydraulic cutting head complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max.



CUTTING CAPACITY			
MATERIAL	TENSILE STRENGTH (daN/mm <sup>2</sup> )	MAX CUTTING DIAMETER (mm)	
ROPES & CONDUCTORS	COPPER	≤ 41	45
	ALUMINIUM	≤ 20	45
	ALDREY	≤ 34	45
	STEEL	≤ 180	INDICATIVE EXAMPLES: 7 x 3,0 : Ø est. = 9,0 mm 19 x 2,1 : Ø est. = 10,5 mm 19 x 2,3 : Ø est. = 11,5 mm
	MULTI STRANDS STEEL (STRANDS Qty ≥ 200)	≤ 180	18
	ACSR	≤ 180	45 INDICATIVE EXAMPLES: 26 x 2,50 + 7 x 1,95 : Ø est. = 15,85 26 x 3,06 + 7 x 2,38 : Ø est. = 19,38 26 x 3,60 + 7 x 2,80 : Ø est. = 22,80 54 x 3,50 + 19 x 2,10 : Ø est. = 31,50 54 x 4,36 + 19 x 2,62 : Ø est. = 39,20
RODS	STEEL	≤ 60	18
		≤ 42	20
	COPPER	≤ 30	30
		≤ 25	32
	ALUMINIUM	≤ 16	45

# HYDRAULIC CUTTING HEAD TC04N

## *Technical characteristics*

### PROPERTIES

Type of action	Cutting
Maximum cutting diameter	45 mm
Nominal pressure	700 bar
Width	100 mm
Length	311 mm
Weight	3.9 kg



## HYDRAULIC CUTTING HEAD TC04N

*In the same kit*

### Storage

**CASE VAL - Metal carrying case VAL 04**

*Products used together*

### Tools

**18V Battery pump B1300PL - B1300PL**