

SUPPORT TROLLEY CS-SD-TA

Track gauges: 1000 to 1700 mm


The support mechanism, which secures the portable drilling machines SD-15PR-ECO, SD-9P-ECO, SD-10E and the portable impact wrench NR-11P, incorporates a gas pressure spring to give a constant, balanced control to the machine during operation.

Fitted with insulated wheels, the trolley does not interfere with the track electrical circuits.

The trolley is easily closed and can comfortably be carried by a single operator.



CERTIFICATES 


 EN 13977

SUPPORT TROLLEY CS-SD-TA

Technical characteristics

PROPERTIES

| | |
|----------|---------|
| Patented | yes |
| Height | 960 mm |
| Length | 1075 mm |
| Weight | 31.5 kg |



SUPPORT TROLLEY CS-SD-TA

Products used together

Tools

Electric drilling machine SD-10E - Electric SD-10E

IMPACT WRENCHES NR

ELECTRIC IMPACT WRENCH NR-13E - IMPACT WRENCHES NR-11P

Petrol Wooden Sleeper Drill SD-15PR-ECO - SD-15PR-ECO

Electric Wooden Sleeper Drill SD-10E-110 - Electric drilling machine SD-10E-110

Petrol engine SD-9P-ECO - SD-9P-ECO

Accessories

Interface kit KCS-NR

Interface kit KHOR-NR