

18.0 V CORDLESS HYDRAULIC CUTTING TOOL B-TC250

Next generation of 18.0 V cordless hydraulic cutting tool specifically designed to cut Copper, aldrej, Aluminium, Aluminium-Steel cables and Steel ropes, Aluminium and Steel rods having a max overall diameter of 25 mm.

The blades are manufactured from high strength special Steel, heat treated to ensure a long service life.

New Li-Ion 18 V 4 Ah batteries offer a higher capacity than 14.4 V 3 Ah, while greater cutting speed and cutting force result from a revitalised hydraulic system with double speed action. The battery is equipped with LED indicators to show the remaining battery life at any time by pressing the adjacent button. The head can rotate through 180 degrees, to enable the operator to work in the most comfortable position, and can easily be opened to allow cutting of running cables. Fitted with a maximum hydraulic pressure valve.



Designed with improved balance, B-TC250 is easily manageable during the cutting process and, by the use of bi-component plastics, has a shell with high resistance to wear and damage. Rubber grip inserts, low noise and minimal vibration aid operator comfort while additional convenience and safety are provided by LED lighting of the working area.

Operating temperature: -15 to +50 ° C

CUTTING CAPACITY			
MATERIAL	TENSILE STRENGTH (daN/mm ²)	MAX CUTTING DIAMETER (mm)	
ROPE & CONDUCTORS	COPPER	≤ 41	25
	ALUMINIUM	≤ 20	25
	ALDREY	≤ 34	25
	STEEL	≤ 180	INDICATIVE EXAMPLES: 7 x 3,0 : Ø est. = 9,0 mm 19 x 2,1 : Ø est. = 10,5 mm 19 x 2,3 : Ø est. = 11,5 mm
	MULTI STRANDS STEEL (STRANDS Qty ≥ 200)	≤ 180	18
	ACSR	≤ 180	25 INDICATIVE EXAMPLES: 26 x 2,50 + 7 x 1,95 : Ø est. = 15,85

			$26 \times 3,06 + 7 \times 2,38 : \varnothing \text{ est.} = 19,38$ $26 \times 3,60 + 7 \times 2,80 : \varnothing \text{ est.} = 22,80$
RODS	STEEL	≤ 60	13
		≤ 42	16
	COPPER	≤ 30	20
		≤ 25	23
	ALUMINIUM	≤ 16	25

The tool is supplied as:

- *Basic tool with battery and shoulder strap*
- *Spare battery*
- *Battery charger*
- *Plastic carrying case suitable for storing the tool and accessories*

CERTIFICATES 

 BT 2006/42/CE

18.0 V CORDLESS HYDRAULIC CUTTING TOOL **B-TC250**

Technical characteristics

PROPERTIES

Type of action	Cutting
Maximum cutting diameter	25 mm
Nominal pressure	600 bar
Battery material	Li-Ion
Battery voltage	18 V
Battery current	4 Ah
Length	300 mm
Width	83 mm
Height	337 mm
Weight	4.65 kg



18.0 V CORDLESS HYDRAULIC CUTTING TOOL **B-TC250**

In the same kit

Accessories

- Shoulder strap 6000354

Tools

Li-Ion high power battery CB1820L Li-Ion high power battery CB1840L

Battery charger ASC30-36 - ASC30-36 EU 27044000