

# 18.0 V CORDLESS HYDRAULIC CUTTING TOOL B-TC500

## *Industrial application*

Next generation of 18.0 V cordless hydraulic cutting tool specifically designed to cut Copper, Aluminium and telecommunication cable having a max overall diameter of 50 mm. The blades are manufactured from high strength special Steel, heat treated to ensure a long service life.

New Li-Ion 18 V 4 Ah batteries offer a higher capacity than 14.4 V 3 Ah, while greater cutting speed and cutting force result from a revitalised hydraulic system with double speed action. The battery is equipped with LED indicators to show the remaining battery life at any time by pressing the adjacent button.

The head can rotate through 90 degrees, to enable the operator to work in the most comfortable position, and can easily be opened to allow cutting of running cables. Fitted with a maximum hydraulic pressure valve.

Designed with improved balance, B-TC500 is easily manageable during the cutting process and, by the use of bi-component plastics, has a shell with high resistance to wear and damage. Rubber grip inserts, low noise and minimal vibration aid operator comfort while additional convenience and safety are provided by LED lighting of the working area.


**Operating temperature: -15 to +50 ° C**

*The tool is supplied as:*

- > Basic tool with battery and shoulder strap
- > Spare battery
- > Battery charger
- > Plastic carrying case suitable for storing the tool and accessories



CERTIFICATES 

 BT 2006/42/CE

# 18.0 V CORDLESS HYDRAULIC CUTTING TOOL **B-TC500**

## *Technical characteristics*

### PROPERTIES

Type of action	Cutting
Battery material	Li-Ion
Battery voltage	18 V
Battery current	4 Ah
Maximum cutting diameter	50 mm
Length	405 mm
Width	83 mm
Height	398 mm
Weight	5.8 kg



# 18.0 V CORDLESS HYDRAULIC CUTTING TOOL **B-TC500**

*In the same kit*

## Accessories

Shoulder strap 6000354

USB cable 6006309

## Tools

Li-Ion high power battery CB1820L    Li-Ion high power battery CB1840L

**Battery charger ASC30-36 - ASC30-36 EU 27044000**

## Storage

**- Plastic case VAL P40**