

18.0 V CORDLESS HYDRAULIC CUTTING TOOL B35M-TC025

OVERHEAD LINE APPLICATION

Can be operated with one hand.
 Balanced for greater control.
 Head rotates 180° for ease of operation in confined spaces.
 Fitted with a maximum pressure valve. Extremely quiet, minimal vibration. Durable moulded body offering high resistance to wear and damage in all operating conditions.
 New Li-Ion 18V 2Ah High Power battery. The battery is equipped with LED indicators to show the remaining battery life at any time by pressing the adjacent button.
 Supplied in a robust plastic case to accommodate the tool and all the accessories.
 Two batteries and charger included.
Operating temperature: -15 to +50 ° C



CUTTING CAPACITY

Material		Tensile strength (daN/mm ²)	Max cutting diameter (mm)
ROPES & CONDUCTORS	COPPER	≤ 41	25
	ALUMINIUM	≤ 20	25
	ALMELEC	≤ 34	25
	STEEL	≤ 180	INDICATIVE EXAMPLES: 19 x 2,1 : Ø est. = 10,5 mm 19 x 2,3 : Ø est. = 11,5 mm
	MULTI STRANDS STEEL (STRANDS Qty ≥ 200)	≤ 180	18
			25 INDICATIVE EXAMPLES: 26 x 2,50 + 7 x 1,95 : Ø

	ACSR	≤ 180	est. = 15,85 26 x 3,06 + 7 x 2,38 : Ø est. = 19,38 26 x 3,60 + 7 x 2,80 : Ø est. = 22,80
RODS	STEEL	≤ 60	10
		≤ 42	-
	COPPER	≤ 30	-
		≤ 25	16
	ALUMINIUM	≤ 16	25

The tool is supplied as:

- > *Basic tool with battery and wrist strap*
- > *Spare battery*
- > *Battery charger*
- > *Plastic carrying case suitable for storing the tool and accessories*

CERTIFICATES 

 BT 2006/42/CE

18.0 V CORDLESS HYDRAULIC CUTTING TOOL B35M-TC025

Technical characteristics

PROPERTIES

Type of action	Cutting
Maximum cutting diameter	25 mm
Battery material	Li-Ion
Battery voltage	18 V
Battery current	2 Ah
Length	391 mm
Width	133 mm
Height	81 mm
Weight	3.1 kg



18.0 V CORDLESS HYDRAULIC CUTTING TOOL **B35M-TC025**

In the same kit

Accessories

- Shoulder strap 6000354

Storage

- Plastic case VAL P22

Tools

- Li-Ion high power battery CB1820L

Battery charger ASC30-36

ASC30-36 AUS/NZ 27046000

ASC30-36 EU 27044000