

18.0 V CORDLESS HYDRAULIC CRIMPING TOOL B35-45MD

Can be operated with one hand.

Balanced for greater control.

Head rotates 180° for ease of operation in confined spaces.

Fitted with a maximum pressure valve.

Extremely quiet, minimal vibration.

Durable moulded body offering high resistance to wear and damage in all operating conditions.

New Li-Ion 18.0V 2.0Ah High Power battery.

The battery is equipped with LED indicators to show the remaining battery life at any time by pressing the adjacent button.

Supplied in a robust plastic case to accommodate the tool and all the accessories.

Two batteries and charger included.

B35-45MD accepts many of the dies common to 45 kN Cembre crimping tools.

B35-45MD specific dies available for crimping 120 mm² and 150 mm².

Operating temperature: -15 à +50 °C



MAIN APPLICATIONS - max section mm ²		
L.V. lugs and splices	“C” sleeve Connectors	H.V. lugs and splices
150	35	70

The tool is supplied as:

- >• *Basic tool with battery and wrist strap*
- >• *Spare battery*
- >• *Battery charger*
- >• *Plastic carrying case suitable for storing the tool and accessories*

18.0 V CORDLESS HYDRAULIC CRIMPING TOOL B35-45MD

Technical characteristics

PROPERTIES

Type of action	Crimp
Battery material	Li-Ion
Battery voltage	18 V
Battery current	2 Ah
Length	354 mm
Height	133 mm
Width	81 mm
Weight	2.19 kg



18.0 V CORDLESS HYDRAULIC CRIMPING TOOL B35-45MD

In the same kit

Storage

- Plastic case VAL P22

Tools

- Li-Ion high power battery CB1820L

Battery charger ASC30-36

ASC30-36 AUS/NZ 27046000

ASC30-36 EU 27044000

Products used together

Connectors

COPPER TUBE CRIMPING LUGS ACCORDING TO DIN 46235 DR

DR10-10	DR10-5	DR10-6
DR10-8	DR120-10	DR120-12
DR120-16	DR120-20	DR120-8
DR150-10	DR150-12	DR150-16
DR150-20	DR16-10	DR16-12
DR16-5	DR16-6	DR16-8
DR25-10	DR25-12	DR25-6
DR25-8	DR35-10	DR35-12
DR35-16	DR35-6	DR35-8
DR50-10	DR50-12	DR50-16
DR50-6	DR50-8	DR6-5
DR6-6	DR6-8	DR70-10
DR70-12	DR70-16	DR70-20
DR70-8	DR95-10	DR95-12
DR95-16	DR95-20	DR95-8

COPPER TUBE CRIMPING LUGS A-M Fine stranded

A12-M10	A12-M10/19	A12-M12
A12-M6/15	A12-M8	A17-M10
A17-M10/19	A17-M12	A17-M14
A17-M16	A17-M6	A17-M8
A20-M10	A20-M12	A20-M14
A20-M16	A20-M8	A29-M10
A29-M12	A29-M14	A29-M16
A29-M20	A29-M8	A9-M10
A9-M12	A9-M6/15	A9-M8

HIGH VOLTAGE COPPER TERMINALS 2A-M

2A10-M10	2A10-M12	2A10-M14
2A10-M16	2A14-M10	2A14-M12
2A14-M14	2A14-M16	2A19-M10
2A19-M12	2A19-M14	2A19-M16
2A19-M20	2A24-M10	2A24-M12
2A24-M14	2A24-M16	2A24-M20
2A30-M10	2A30-M14	2A30-M16
2A30-M20	2A3-M10	2A3-M8
2A5-M10	2A5-M12	2A5-M8
2A7-M10	2A7-M12	2A7-M8

SLEEVE CONNECTORS C-C

C10-C10	C10-C10ST	C16-C16
C16-C16ST	C25-C10	C25-C10ST
C25-C25	C25-C25ST	C35-C16
C35-C16ST	C35-C35	C35-C35ST
C6-C6	C6-C6ST	

COPPER TUBE CRIMPING LUGS A-M

A10-M10	A10-M12	A10-M14
A10-M16	A10-M6	A10-M8
A14-M10	A14-M12	A14-M14
A14-M16	A14-M6	A14-M8
A19-M10	A19-M12	A19-M14
A19-M16	A19-M20	A19-M6
A19-M8	A1-M10	A1-M3
A1-M3.5	A1-M4	A1-M5
A1-M6	A1-M8	A24-M10
A24-M12	A24-M14	A24-M16
A24-M20	A24-M8	A2-M10
A2-M12	A2-M4	A2-M5
A2-M6	A2-M8	A30-M10
A30-M12	A30-M14	A30-M16
A30-M20	A30-M8	A3-M10
A3-M12	A3-M4	A3-M5
A3-M6	A3-M8	A5-M10
A5-M12	A5-M4	A5-M5
A5-M6	A5-M8	A7-M10
A7-M12	A7-M5	A7-M6
A7-M8		

COPPER TUBE CRIMPING LUGS ANGLED 90° A-L

A10-L10	A10-L12	A10-L6
A10-L8	A14-L10	A14-L12
A14-L16	A14-L8	A19-L10
A19-L12	A19-L8	A1-L6
A24-L10	A24-L12	A2-L5
A2-L6	A2-L8	A30-L10
A30-L12	A3-L10	A3-L5
A3-L6	A3-L8	A5-L10
A5-L6	A5-L8	A7-L10
A7-L12	A7-L6	A7-L8

RING TONGUE TERMINALS WITH CONTAINED PALM A-M Contained palm

A10B-M6/11.5	A14B-M6/11.5	A19B-M8/15.5
A19-M10/19	A24B-M10/19	A24B-M8/19
A2-M5/9	A30B-M10/19	A30B-M8/19
A3-M5/9	A5-M5/9	A7B-M6/11.5

UNINSULATED PIN CONNECTORS A-P

A10-P25	A14-P30	A2-P12
A3-P14	A5-P16	A7-P20

Through connectors

CRIMPING THROUGH CONNECTORS ACCORDING TO DIN 46267 T.1 DSV

DSV10	DSV120	DSV150
DSV16	DSV25	DSV35
DSV50	DSV6	DSV70
DSV95		

THROUGH CONNECTORS L-M

L10-M	L14-M	L19-M
L24-M	L2-M	L30-M
L3-M	L5-M	L7-M

PARALLEL CONNECTORS L-P

L10-P	L14-P	L19-P
L1-P	L24-P	L2-P
L30-P	L3-P	L5-P
L7-P		

Tools
CRIMPING FORCE GAUGES FOR HYDRAULIC TOOLS MPC7 - MPC7