

18.0 V CORDLESS HYDRAULIC CUTTING TOOL B-TC250BS

Max cutting Ø 26 mm

Can be operated with one hand.

Balanced for greater control.

Head rotates 180° for ease of operation in confined spaces.
 The open head and the "scissor" movement of the blades facilitate the cutting of running cables.
 Fitted with a maximum pressure valve.
 Extremely quiet, minimal vibration. Durable moulded body offering high resistance to wear and damage in all operating conditions.
 New Li-Ion 18V 2Ah High Power battery. The battery is equipped with LED indicators to show the remaining battery life at any time by pressing the adjacent button.



CUTTING CAPACITY - a few examples

Section	Ø	CABLE TYPE
mm ²	mm	
120	13,34 mm	RIM120
95	-	Steel cable with Bitum (DIEPA)
95	-	Steel cable Lidra
-	~ 10	10 mm grounding wire with insulation
50	~ 8,85	Bronze
70	~ 10,3	Bronze
95	~ 12,5	Bronze
70	~ 10,5	Aluminium
95	~ 12,5	Aluminium
150	~ 15,8	Aluminium
35/6	~ 8,0	Aluminium-steel

50/8	~ 9,5	Aluminium-steel
50/3	~ 11,5	Aluminium-steel
70/12	~ 11,8	Aluminium-steel
95/15	~ 13,8	Aluminium-steel
150/25	~ 17,0	Aluminium-steel
230/30	~ 21,0	Aluminium-steel
265/35	~ 23,0	Aluminium-steel

Supplied in a robust plastic case to accommodate the tool and all the accessories.
Two batteries and charger included.
Operating temperature: -15 to +50 ° C

The tool is supplied as:

- > *Basic tool with battery and wrist strap*
- > *Spare battery*
- > *Battery charger*
- > *Plastic carrying case suitable for storing the tool and accessories*

18.0 V CORDLESS HYDRAULIC CUTTING TOOL **B-TC250BS**

Technical characteristics

PROPERTIES

Type of action	Cutting
Maximum cutting diameter	26 mm
Battery material	Li-Ion
Battery voltage	18 V
Battery current	2 Ah
Length	436 mm
Height	140 mm
Width	81 mm
Weight with battery	3.4 kg



18.0 V CORDLESS HYDRAULIC CUTTING TOOL **B-TC250BS**

In the same kit

Tools

- Li-Ion high power battery **CB1820L**

Battery charger ASC30-36

ASC30-36 AUS/NZ 27046000 ASC30-36 EU 27044000

Storage

- Plastic carrying case **VAL P48**