


**COMPRESSION CABLE GLANDS
POLYAMIDE PA6 - I400 SERIES**
BSP thread ISO 228/1

Ref. Light Grey	P	Fixing Hole Ø (mm)	Ø A min-max (mm)	B1 Spanner (mm)	B2 Spanner (mm)	C (mm)	L min-max (mm)	Quantity Box/Bag
1400	G1/4"	13,5	5,5- 7	15	16	8	16-20	300/100
* 1401	G3/8"	17	6,5- 8,5	17	20	8	19-22	200/100
* 1401B	G3/8"	17	8 -10	19	22	8	18-24	100/100
* 1401C	G3/8"	17	10 -12	22	24	9	22-26	100/100
* 1402	G1/2"	21,5	8 -11	21	24	9	22-26	100/100
1403	G5/8"	23,5	11 -14	23	27	10	24-33	50/50
1404	G3/4"	27	14,5-18	30	33	11	25-32	50/25
1405	G1"	34	17 -22	34	38	11,5	27-35	20/10
1407	G1"1/2	48	30 -34	50	53	14	33-42	10/10
1408	G2"	60	38 -44	60	65	14,5	37-48	5/5

*Add to Ref: N for Black

Technical details:

MATERIAL :

POLYAMIDE 6

PROTECTION :

IP 54 (EN 60529:1991 / CEI 70-1)

SELF-EXTINGUISHING CLASS :

V0 (UL 94)

TEMPERATURE RANGE :

-20°C ÷ +90°C (continuous)

GLOW-WIRE TEST (2 mm) :

960°C (EN 60695-2-1/1:1996 / CEI 89-13)

Resistance to chemical:

STRONG ACIDS - not resistant

SOFT ALKALINES - not resistant

STRONG ALKALINES - not resistant

IDROCARBONS - resistant

CHLORIDES - not resistant

ALCOHOLS - resistant

KETONES - resistant

Cembre SpA

Via Serenissima, 9 - 25135 Brescia (Italy)

Tel.: +39 030 36921 - Fax: +39 030 3365766

 Web: www.cembre.com - Email: info@cembre.com