



INSULATED CHAIN TERMINALS "CP" RANGE WITH EASY ENTRY









GENERAL INFORMATIONS










- The terminals are for use for internal wiring of equipment only.
- The terminals are for use with Cu wire.
- 600V max. building wiring, 1000V max. in sign and fixtures.
- The maximum operating temperature is 105°C.
- Manufactured from electrolytic copper strip, annealed to guarantee optimum ductility and electrolytically tin plated to avoid oxidation.
- Developed for use with production machinery, to give a quick and reliable crimped joint.
- The unique shape of PC sleeve, a halogen free self extinguishing plastic material, guarantees total insertion of the conductor strands into the terminal barrel.
- The internal surface of barrel is rifled to improve contact with conductor strands when crimped and to increase tensile strength.

- The CP range of terminals offers a wide selection of rings, forks, pins and blades, designed to meet ever changing requirements of the end users.

INSTALLATION INSTRUCTIONS

- 1) Select the proper connector for the wire size used.
- 2) Select the proper applicator head as indicated in the table below.
- 3) Strip the cable insulation, to expose a length of conductor as recommended in the table below, taking care not to damage or cut any of the strands.
- 4) Crimp the connector as indicated in the operation and maintenance manual of the tool.

CATALOG NUMBER	TYPE	SLEEVE COLOR CODE	STUD SIZE	CONDUCTOR mm ² (AWG) 	CABLE STRIP LENGTH mm 	INSTALLATION TOOLING & DIE
CRP-M3		RED	M3	0.25 ÷ 1.5 (22 ÷ 16)	5 ÷ 6	ELB-2 ELB-3 ELB-3Y BENCH PRESS & RA-2 RA-3 APPLICATOR HEAD
CRP-M3,5			M3,5			
CRP-M3,5/1			M3,5			
CRP-M4			M4			
CRP-M4/3			M4			
CRP-M5			M5			
CRP-M6			M6			
CRP-M6/1			M6			
CRP-M7	M7					
CRP-M8	M8					
CRP-U3			M3			
CRP-U3,5			M3,5			
CRP-U3,5/2			M3,5			
CRP-U4			M4			
CRP-U4/1			M4			
CRP-U4/2			M4			
CRP-U5			M5			
CRP-U6			M6			
CRP-U6/1	M6					
CRP-U8	M8					
CRP-P8						
CRP-P10						
CRP-P12						
CRP-PP12						
CRP-PP12/1						
CRP-PP12/23						
CRP-PP14						

CATALOG NUMBER	TYPE	SLEEVE COLOR CODE	STUD SIZE	CONDUCTOR mm ² (AWG) 	CABLE STRIP LENGTH mm 	INSTALLATION TOOLING & DIE		
CBP-M3		BLUE	M3	1.5 ÷ 2.5 (16 ÷ 14)	5 ÷ 6	ELB-2 ELB-3 ELB-3Y BENCH PRESS & BA-2 BA-3 APPLICATOR HEAD		
CBP-M3,5			M3,5					
CBP-M3,5/1			M3,5					
CBP-M4			M4					
CBP-M5			M5					
CBP-M6			M6					
CBP-M6/1			M6					
CBP-M7			M7					
CBP-M8	M8							
CBP-U3			M3					
CBP-U3,5			M3,5					
CBP-U4			M4					
CBP-U4/1			M4					
CBP-U4/2			M4					
CBP-U5			M5					
CBP-U6	M6							
CBP-P8								
CBP-P10								
CBP-P12								
CBP-PP12								
CBP-PP12/25								
CGP-M3			YELLOW	M3	4 ÷ 6 (12 ÷ 10)	8 ÷ 9	ELB-2 ELB-3 ELB-3Y BENCH PRESS & GA-2 GA-3 APPLICATOR HEAD	
CGP-M3,5				M3,5				
CGP-M4				M4				
CGP-M5		M5						
CGP-M6		M6						
CGP-M6/1		M6						
CGP-M7		M7						
CGP-M8		M8						
CGP-M8/1	M8							
CGP-U3,5		M3,5						
CGP-U4		M4						
CGP-U5		M5						
CGP-U6		M6						
CGP-P10								
CGP-P12								
CGP-P14								
CGP-PP12								
CGP-PP17								



Cembre ——— www.cembre.com



Cembre S.p.A.
Via Serenissima, 9
25135 Brescia (Italia)
Telefono: 030 36921
Telefax: 030 3365766
E-mail: sales@cembre.com
www.cembre.it

Cembre Ltd.
Dunton Park
Kingsbury Road, Curdworth - Sutton Coldfield
West Midlands B76 9EB (UK)
Tel.: 01675 470440 - Fax: 01675 470220
E-mail: sales@cembre.co.uk
www.cembre.co.uk

Cembre S.a.r.l.
22 Avenue Ferdinand de Lesseps
91420 Morangis (France)
Tél.: 01 60 49 11 90 - Fax: 01 60 49 29 10
CS 92014 - 91423 Morangis Cédex
E-mail: info@cembre.fr
www.cembre.fr

Cembre España S.L.U.
Calle Verano, 6 y 8 - Pl. Las Monjas
28850 Torrejón de Ardoz - Madrid (España)
Telefono: 91 4852580
Telefax: 91 4852581
E-mail: comercial@cembre.es
www.cembre.es

Cembre GmbH
Heidemannstraße 166
80939 München (Deutschland)
Telefon: 089 3580676
Telefax: 089 3580677
E-mail: sales@cembre.de
www.cembre.de

Cembre Inc.
Raritan Center Business Park
181 Fieldcrest Avenue
Edison, New Jersey 08837 (USA)
Tel.: 732 225-7415 - Fax: 732 225-7414
E-mail: Sales.US@cembreinc.com
www.cembreinc.com