



CEMBRE

**BA600C CRIMPING IS NOW
SIMPLER. FASTER. SMARTER.**



www.cembre.com



BA600C



The new BA600C is the ideal tool for crimping connectors up to 300 mm².

Equipped with the **ADAPTIVE CONTROL** function, it guarantees optimisation of the crimping cycle, automatically interrupting the cycle when the two dies come into contact with each other.

This innovative approach eliminates the need to reach maximum pressure at each cycle, as is the case with traditional tools, reducing tool wear and ensuring the same quality standards as maximum pressure crimping.

The advantages?

- **Less mechanical stress on the tool and longer component life**
- **Energy savings and longer battery life**
- Analysis of the reduction in energy consumption compared to the standard cycle, indicating the percentage saved (**SAVED ...%**).
- **HOLD function**, thanks to which the tool stops automatically when the dies come into contact with the connector, without deforming it.

A smart solution for precise, efficient and long-lasting operations.



BA600C / HIGHLIGHTS



Adaptive Control (AC)



HOLD function



Electronic Pressure Sensor (EPS)



SMARTOOL Technology



Multifunction OLED display with capacitive touch button



STEEL body and driving mechanism



+30,000 adaptive cycles* for maintenance (*equivalent to 100,000 cycles performed on a medium-section connector)



Dual-speed feed system



BA600C / SMART CRIMPING

Adaptive control



Adaptive control allows the crimping cycle to be completed when the two dies come into contact with each other, an essential condition for correct crimping.

Operational data acquisition technology



SMARTOOL technology records the operating data, work cycles and errors/malfunctions in the internal memory, all of which can be downloaded to a PC.

Always reliable and precise



The EPS electronic control system ensures precision and repeatability of the crimping cycles as it relies on a sensor dedicated to controlling and commanding the end-of-cycle function.



Display of parameters



Using the OLED display, the operator can view different parameters, including:

- Pressure developed
- Battery charge
- General operating information
- Number of work cycles
- Number of cycles before maintenance



HOLD function



This function holds the connector between the dies without compressing it, facilitating the insertion of the conductor into the connector and verification of correct positioning before crimping.



Adaptive service



The service interval of 30,000 cycles refers to standard tool operation. With the adaptive function enabled, this value is recalculated based on the pressure reached, expressing only the fraction of use actually employed, and bringing the service interval to 100,000 cycles when used on medium-section connectors.



BA600C / SAFE AND PRACTICAL



Comfort and convenience for the operator

The design, reduced weight and mass balance make it easy to use.

Stop accidental activation

The mechanically protected start button and double-clicking requirement on start-up ensure operator safety.

Pressure release

Manual pressure release can be operated at any stage of compression.

Robust and durable

The stainless steel body guarantees greater durability and reliability of the tool over time.



Two-component shell

The two-component plastic shell ensures mechanical protection in all conditions of use.

Double hydraulic speed

The patented dual-speed pumping system ensures reduced cycle times, energy savings, speed, and working autonomy.

Double safety for the user

The tool is equipped with a maximum pressure valve as an additional safety feature in addition to the internal pressure transducer (EPS).

No overheating

The air flows inside the tool have been optimised to ensure proper cooling of the components, allowing the tool to operate even under particularly heavy workloads.

BA600C / THE CONNECTORS

COPPER

DR-N



COMPRESSION CABLE LUGS ACCORDING TO DIN 46235

HR-N



COMPRESSION CABLE LUGS

A-M



COMPRESSION CABLE LUGS

T-M



COMPRESSION CABLE LUGS ACCORDING TO NF C 20-130

COPPER

1020
1021
1030
1040
1051
1052

COMPRESSION JOINTS AND CONNECTORS ACCORDING TO DIN 46230 - 46234 - 46341



1030
1031



PRE-INSULATED CONNECTORS IN PA6.6

PK



PRE-INSULATED END SLEEVES IN PA6

ALUMINIUM

AAD
DSVA
CAAD-M
MTA-C

ALUMINUM CABLE LUGS AND JOINTS ACCORDING TO DIN46329 and DIN46267/2 AND BI-METALLIC CABLE LUGS ACCORDING TO DIN46329



BA600C / THE DIES



	Connector Type	Conductor cross-section mm ²	Die Type	Impression Type	
COPPER	DR-N; DSV		6 - 300	MK...-60C	
	HR-N; HSV		6 - 300	MH...-60C	
	A-M; L-M		4 - 300	ME...-60C	
	T-M; L-T		4 - 300	MS...-60C	
	Q		6 - 120	MQ...-60C	
	1020; 1021; 1030; 1040; 1051; 1052		10 - 120	MQ...-60C	
	1030; 1031		10 - 50	MQIS...-60C	
	PK; KE		0.3 - 120	MT...-60C	
ALUMINIUM	AAD; DSVA; CAAD-M; MTA-C		10 - 300	MK...B-60C	
	PRE-ROUNDING		25 - 240	UP...-60C	

Included in the package:

- Cordless base tool, shoulder strap
- Spare battery
- Battery charger
- USB cable
- Modular hard plastic case suitable for storing the tool and its accessories





www.cembre.com



CEMBRE S.p.A.

via Serenissima, 9
25135 Brescia
Italy
Ph +39 030 36921
ufficio.vendite@cembre.com
sales@cembre.com

CEMBRE Ltd.

Dunton Park,
Kingsbury Road,
Curdworth,
Sutton Coldfield,
West Midlands, B76 9EB
United Kingdom
Ph +44 01675 470440
sales@cembre.co.uk

CEMBRE S.A.R.L.

Tour Part-Dieu
129 rue Servient
69003 Lyon
France
Ph +33 04 20 93 01 70
info@cembre.fr

CEMBRE, S.L.U

Calle Verano 6 y 8
Pl Las Monjas
28850 Torrejón de Ardoz
Madrid - Spain
Ph +34 91 4852580
comercial@cembre.es

CEMBRE GmbH

Geschäftsbereich
Energie- und Bahntechnik
Heidemannstr. 166
80939 München - Germany
Ph + 49 89-3580676
info@cembre.de

Geschäftsbereich
Industrie und Handel
Boschstraße 7
71384 Weinstadt - Germany
Ph +49 7151-20536-60
info-w@cembre.de

CEMBRE B.V.

Luchthavenweg 53
5657EA Eindhoven
The Netherlands
Ph +31 (0) 40 311 1937
info@cembre.nl

CEMBRE, INC.

Raritan Center Business Park
300 Columbus Circle-S.F.
Edison, NJ 08837 USA
Ph +1 (732) 225-7415
sales.us@cembre.com

**Cembre Electrical
Connections Shanghai Limited**

Room 2111,
Jin Hang Mansion, NO.83
Wan Hang Du Road,
Jing An District,
Shanghai
Ph +86-2160195778
info@cembre.cn
sales@cembre.cn

