



CEMBRE

LD-16B-RP RAINPROOF ECODRILL
BEST SOLUTION FOR RAIL DRILLING



LD-16B-RP / ECODRILL ONE MORE BATTERY



CEMBRE offers a full range of machinery for the **maintenance of rail lines**.
The range comprises:

TW-18B
Torque
controlled
wrench
Rainproof



36V
Li-HD
battery



NR-25B
Impact
wrench
Rainproof



SD-36B
Sleeper drill
Rainproof




B70M-P36R
Portable
electro-hydraulic pump
Rainproof



All equipped with the same rechargeable battery system, giving users an enormous advantage.
All designed to work in all weather conditions.

LD-16B-RP / ECODRILL



ERGONOMIC DESIGN

Weighing less than 20 kg with the over rail clamp attached, CEMBRE LD-16B-RP rail drills are easily transported via the balanced carrying handle and are compact in design allowing operation in narrow spaces.



COOLING SYSTEM

The drills are provided with a coolant system consisting of a reservoir and pump for use with suitable cooling lubricants.



ADVANCE LEVER

The starting point of the advance lever can be easily adjusted for either left hand or right hand drilling operations.



QUICK FIT CLAMP

Quick fastening and unfastening system integrated in the over rail clamp device.




FAST-FIT CHUCK

Faster drilling when using CY broach cutters with FAST-FIT shanks; quicker cutter replacement without tooling.



DOUBLE-SIDED TEMPLATE KITS

KPAF template kits are equipped with a double profile that enables quick positioning of the drill on two different rail types by simply loosening the wing nuts and inverting the inserts.



LD-16B-RP / ECODRILL



LD is the best solution for rail drilling in all respects: no emission of harmful gases, low noise and vibration impact, high battery efficiency and very high execution speed.

These features make it ideal for working in closed environments, such as tunnels and underground lines, and for night work. The smart power-reading system acts as a drilling assistant by informing the operator, via the LED display colour, how much force must be applied to the advance lever.

The battery is compatible with the wrenches, **SD-36B** sleeper drill and **B70M-P36R** pump.

FEATURES

drilling range	Ø 7 ÷ 40 mm
with special spiral bits on rail up to 45 mm thick	Ø 7 ÷ 33 mm
with broach cutters on rail up to 50 mm thick	Ø 13 ÷ 33 mm
max. rail web thickness	50 mm
speed of the shaft without load	260 revs/min
power supply	36 V =
dimensions (LxWxH)	489 x 271 x 485 mm
weight with battery and over rail clamp DBG-F2	19,2 kg
ingress protection	IP44M

SALE SETUP

drilling machine	LD-16B-RP
2 batteries 36V-8Ah Li-Ion	CB3680L
battery charger	ASC145-EU
canvas bag for batteries and battery charger	CVB-032
over rail clamp	DBG-F2
accessories kit	✓
coolant unit	SR5000

CASE ON REQUEST

plastic case	VAL-P24
wheeled plastic case	VAL-P24-CS
metal case	VAL-LD-L

- Complete 33 mm drilling time 15 seconds
- 40x19mm holes with one charge
- 36V CEMBRE system
- Brushless motor
- Electronic drill assistant with coloured LED



Cod. 6260736



www.cembre.com



CEMBRE S.p.A.
via Serenissima, 9
25135 Brescia
Italy
Ph +39 030 36921
ufficio.vendite@cembre.com
sales@cembre.com

CEMBRE Ltd.
Dunton Park,
Kingsbury Road,
Curdworth, Sutton Coldfield,
West Midlands, B76 9EB
United Kingdom
Ph +44 01675 470440
sales@cembre.co.uk

CEMBRE S.a.r.l.
22 Avenue Ferdinand
de Lesseps
91420 Morangis Cedex
France
Ph +33 01 60 49 11 90
info@cembre.fr

CEMBRE España S.L.U.
Calle Verano 4 y 8
Pl Las Morjas
28850 Torrejón de Ardoz
Madrid - Spain
Ph +34 91 4852580
comercial@cembre.es

CEMBRE GmbH
Geschäftsbereich
Energie- und Bahntechnik
Heidemannstr. 1.66
80939 München
Germany
Ph +49 89-3580676
info@cembre.de

CEMBRE GmbH
Geschäftsbereich
Industrie und Handel
Boschstraße 7
71384 Weinstadt
Germany
Ph +49 7151-20536-60
info-w@cembre.de

CEMBRE Inc.
Raritan Center Business Park
300 Columbus Circle-S.F.,
Edison, NJ 08837 USA
Ph +1 (732) 225-7415
sales.us@cembre.com
Midwest Office
1051 Perimeter Dr #470
Schaumburg, IL 60173

