



## FEMALE DISCONNECT TERMINALS F-FP

*female connectors, fully reinforced with copper sleeve fully insulated terminals*



CERTIFICATES 

 According to UL 486A standard (file E125401)  BT 2006/95/CE

# FEMALE DISCONNECT TERMINALS F-FP






## *Technical characteristics*






Easy entry	yes
Min operating temperature range	-4 °F
Max operating temperature range	239 °F
Max operating temperature range (surge)	266 °F
Dimensional form	Female terminal
Halogen Free	yes
Material (Body)	Electrolytic copper
Material (Insulated)	PVC



# FEMALE DISCONNECT TERMINALS F-FP

## List of products

<b>RF-FP</b> Cable type: copper, Minimum section: 22 AWG, Maximum section: 16 AWG							
Type	Color	Width	Length	Height of the hooked	Pack qty	Min. pack qty	
RPF-111FIFD		0.02 in.	0.11 in.		2,500	100	
RPF-110FIFD		0.03 in.	0.11 in.		2,500	100	
RPF-188FIFD		0.02 in.	0.19 in.		2,000	100	
RPF-187FIFD		0.03 in.	0.19 in.		2,000	100	
RPF-250FIFD		0.03 in.	0.25 in.		1,500	100	

<b>RF-FP</b> Cable type: flexible copper, Minimum section: 22 AWG, Maximum section: 16 AWG							
Type	Color	Width	Length	Height of the hooked	Pack qty	Min. pack qty	
RPF-111FIFD		0.02 in.	0.11 in.		2,500	100	
RPF-110FIFD		0.03 in.	0.11 in.		2,500	100	
RPF-188FIFD		0.02 in.	0.19 in.		2,000	100	
RPF-187FIFD		0.03 in.	0.19 in.		2,000	100	
RPF-250FIFD		0.03 in.	0.25 in.		1,500	100	

<b>BF-FP</b> Cable type: copper, Minimum section: 16 AWG, Maximum section: 14 AWG							
Type	Color	Width	Length	Height of the hooked	Pack qty	Min. pack qty	
BPF-187FIFD		0.03 in.	0.19 in.		2,000	100	
BPF-250FIFD		0.03 in.	0.25 in.		1,500	100	

<b>BF-FP</b> Cable type: flexible copper, Minimum section: 16 AWG, Maximum section: 15 AWG							
Type	Color	Width	Length	Height of the hooked	Pack qty	Min. pack qty	
BPF-187FIFD		0.03 in.	0.19 in.		2,000	100	
BPF-250FIFD		0.03 in.	0.25 in.		1,500	100	

**GF-FP** *Cable type: copper, Minimum section: 12 AWG, Maximum section: 10 AWG*

Type	Color	Width	Length	Height of the hooked	Pack qty	Min. pack qty
YPF-250FIFD		0.03 in.	0.25 in.		1,000	100

**GF-FP** *Cable type: flexible copper, Minimum section: 12 AWG, Maximum section: 10 AWG*

Type	Color	Width	Length	Height of the hooked	Pack qty	Min. pack qty
YPF-250FIFD		0.03 in.	0.25 in.		1,000	100