


MALE DISCONNECT TERMINALS F-MP



CERTIFICATES 

 BT 2006/95/CE

MALE DISCONNECT TERMINALS F-MP

Technical characteristics

Easy entry	yes
Min operating temperature range	-4 °F
Max operating temperature range	239 °F
Max operating temperature range (surge)	266 °F
Dimensional form	Male terminal
Halogen Free	yes
Material (Body)	Electrolytic copper
Material (Partially reinforced)	PVC



MALE DISCONNECT TERMINALS F-MP

List of products

RF-MP Cable type: flexible copper, Minimum section: 22 AWG, Maximum section: 16 AWG

Type	Color	Width	Length	Height of the hooked	Pack qty	Min. pack qty
RPF-250FIMD		0.03 in.	0.25 in.		1,000	100

RF-MP Cable type: copper, Minimum section: 22 AWG, Maximum section: 16 AWG

Type	Color	Width	Length	Height of the hooked	Pack qty	Min. pack qty
RPF-250FIMD		0.03 in.	0.25 in.		1,000	100

BF-MP Cable type: copper, Minimum section: 16 AWG, Maximum section: 14 AWG

Type	Color	Width	Length	Height of the hooked	Pack qty	Min. pack qty
BPF-250FIMD		0.03 in.	0.25 in.		1,000	100

BF-MP Cable type: flexible copper, Minimum section: 16 AWG, Maximum section: 15 AWG

Type	Color	Width	Length	Height of the hooked	Pack qty	Min. pack qty
BPF-250FIMD		0.03 in.	0.25 in.		1,000	100