

MALE/FEMALE CONNECTORS AND BULLET F-BF

*polycarbonate
insulated terminals -
partially reinforced with copper sleeve*



CERTIFICATES 

 BT 2006/95/CE

MALE/FEMALE CONNECTORS AND BULLET F-BF

Technical characteristics


Easy entry	yes
Min operating temperature range	-4 °F
Max operating temperature range	239 °F
Max operating temperature range (surge)	266 °F
Dimensional form	Female socket connector
Halogen Free	yes




MALE/FEMALE CONNECTORS AND BULLET F-BF

List of products


RF-BF Cable type: flexible copper, Minimum section: 22 AWG, Maximum section: 16 AWG

Type	Color	Diameter	Length	Pack qty	Min. pack qty	
RPF-BF5/32			0.16 in.	1,000	100	

RF-BF Cable type: copper, Minimum section: 22 AWG, Maximum section: 16 AWG

Type	Color	Diameter	Length	Pack qty	Min. pack qty	
RPF-BF5/32			0.16 in.	1,000	100	

BF-BF Cable type: copper, Minimum section: 16 AWG, Maximum section: 14 AWG

Type	Color	Diameter	Length	Pack qty	Min. pack qty	
RPF-BF13/64			0.98 in.	800	100	

BF-BF Cable type: flexible copper, Minimum section: 16 AWG, Maximum section: 15 AWG

Type	Color	Diameter	Length	Pack qty	Min. pack qty	
RPF-BF13/64			0.98 in.	800	100	