


FLEXIBLE BRAIDS FL-ST

Flexible braids are manufactured from electrolytic copper wire. Braids of different conductor sizes or lengths are available on request. Standard finish - bright copper. Flexible braids can be supplied tin plated, in this case add the suffix "ST" to reference.



CERTIFICATES 


 2011/65/EU

FLEXIBLE BRAIDS FL-ST

Technical characteristics

Material (Body)


Tinned electrolytic copper electrolytically



FLEXIBLE BRAIDS FL-ST

List of products

FL-ST



Type	Width	N	Length	Hole diameter	Pack qty
FL10-150ST	0.67 in.	0.39 in.	5.91 in.	0.33 in.	50
FL10-200ST	0.67 in.	0.39 in.	7.87 in.	0.33 in.	50
FL10-250ST	0.67 in.	0.39 in.	9.84 in.	0.33 in.	50
FL16-150ST	0.67 in.	0.39 in.	5.91 in.	0.33 in.	50
FL16-200ST	0.67 in.	0.39 in.	7.87 in.	0.33 in.	50
FL16-250ST	0.67 in.	0.39 in.	9.84 in.	0.33 in.	50
FL16-320ST	0.67 in.	0.39 in.	12.6 in.	0.33 in.	50
FL16-350ST	0.67 in.	0.39 in.	13.78 in.	0.33 in.	50
FL16-420ST	0.67 in.	0.39 in.	16.54 in.	0.33 in.	50
FL16-570ST	0.67 in.	0.39 in.	22.44 in.	0.33 in.	50
FL16-660ST	0.67 in.	0.39 in.	25.98 in.	0.33 in.	50
FL25-150ST	0.83 in.	0.39 in.	5.91 in.	0.33 in.	50
FL25-200ST	0.83 in.	0.39 in.	7.87 in.	0.33 in.	50
FL25-250ST	0.83 in.	0.39 in.	9.84 in.	0.33 in.	50
FL25-300ST	0.83 in.	0.39 in.	11.81 in.	0.33 in.	50