

SINGLE POLE TERMINAL BLOCKS Z6

*indirect clamping
nominal section 10 AWG*

3, 5, 6 and 10 way, single pole terminal blocks for conductor section 17 to 10 AWG. Self contained and robust, they are quick and easy to install for both industrial and domestic use. The indirect clamping of the "ZETApiù" terminal blocks guarantees a low and stable contact resistance. Indirect clamping eliminates damage to the conductor strands. The easy-entry receptacles also grant a fast and reliable insertion of the cable.



CERTIFICATES 



EN 60998-2-1:1993



EN 60998-1:2004



CEI EN 60998-1



CEI 23-21



EN

60998-1



EN 60998-2-1

SINGLE POLE TERMINAL BLOCKS **Z6**

Technical characteristics

Easy entry	yes
UL94 class	V0
IP protection	20
Halogen Free	yes
Impulse voltage	450 V
Max application temperature	185 °F
Material (Body)	Polycarbonate
Material (Clamps)	Electroplated galvanized steel
Material (Connection plate)	ETP Copper electrolytically tinned



SINGLE POLE TERMINAL BLOCKS Z6

List of products

Z6 Cable type: copper, Minimum section: 17 AWG, Maximum section: 17 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z6-3	1.08 in.	0.91 in.	0.91 in.	3	30	0.03 lbs.	
Z6-3D	1.44 in.	0.91 in.	1.57 in.	3	10	0.04 lbs.	yes
Z6-5	1.08 in.	1.38 in.	0.91 in.	5	20	0.05 lbs.	
Z6-5D	1.44 in.	1.38 in.	1.57 in.	5	10	0.06 lbs.	yes
Z6-6	1.12 in.	0.91 in.	1.69 in.	6	15	0.06 lbs.	
Z6-6D	1.3 in.	0.91 in.	2.09 in.	6	10	0.07 lbs.	yes
Z6-10	1.12 in.	1.38 in.	1.69 in.	10	10	0.09 lbs.	
Z6-10D	1.3 in.	1.38 in.	2.09 in.	10	15	0.1 lbs.	yes

Z6 Cable type: flexible copper, Minimum section: 17 AWG, Maximum section: 17 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z6-3	1.08 in.	0.91 in.	0.91 in.	3	30	0.03 lbs.	
Z6-3D	1.44 in.	0.91 in.	1.57 in.	3	10	0.04 lbs.	yes
Z6-5	1.08 in.	1.38 in.	0.91 in.	5	20	0.05 lbs.	
Z6-5D	1.44 in.	1.38 in.	1.57 in.	5	10	0.06 lbs.	yes
Z6-6	1.12 in.	0.91 in.	1.69 in.	6	15	0.06 lbs.	
Z6-6D	1.3 in.	0.91 in.	2.09 in.	6	10	0.07 lbs.	yes
Z6-10	1.12 in.	1.38 in.	1.69 in.	10	10	0.09 lbs.	
Z6-10D	1.3 in.	1.38 in.	2.09 in.	10	15	0.1 lbs.	yes

Z6 Cable type: flexible copper, Minimum section: 15 AWG, Maximum section: 15 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z6-3	1.08 in.	0.91 in.	0.91 in.	3	30	0.03 lbs.	
Z6-3D	1.44 in.	0.91 in.	1.57 in.	3	10	0.04 lbs.	yes
Z6-5	1.08 in.	1.38 in.	0.91 in.	5	20	0.05 lbs.	
Z6-5D	1.44 in.	1.38 in.	1.57 in.	5	10	0.06 lbs.	yes
Z6-6	1.12 in.	0.91 in.	1.69 in.	6	15	0.06 lbs.	
Z6-6D	1.3 in.	0.91 in.	2.09 in.	6	10	0.07 lbs.	yes
Z6-10	1.12 in.	1.38 in.	1.69 in.	10	10	0.09 lbs.	
Z6-10D	1.3 in.	1.38 in.	2.09 in.	10	15	0.1 lbs.	yes

Z6 Cable type: copper, Minimum section: 15 AWG, Maximum section: 15 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z6-3	1.08 in.	0.91 in.	0.91 in.	3	30	0.03 lbs.	
Z6-3D	1.44 in.	0.91 in.	1.57 in.	3	10	0.04 lbs.	yes
Z6-5	1.08 in.	1.38 in.	0.91 in.	5	20	0.05 lbs.	
Z6-5D	1.44 in.	1.38 in.	1.57 in.	5	10	0.06 lbs.	yes
Z6-6	1.12 in.	0.91 in.	1.69 in.	6	15	0.06 lbs.	
Z6-6D	1.3 in.	0.91 in.	2.09 in.	6	10	0.07 lbs.	yes
Z6-10	1.12 in.	1.38 in.	1.69 in.	10	10	0.09 lbs.	
Z6-10D	1.3 in.	1.38 in.	2.09 in.	10	15	0.1 lbs.	yes

Z6 Cable type: copper, Minimum section: 13 AWG, Maximum section: 13 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z6-3	1.08 in.	0.91 in.	0.91 in.	3	30	0.03 lbs.	
Z6-3D	1.44 in.	0.91 in.	1.57 in.	3	10	0.04 lbs.	yes
Z6-5	1.08 in.	1.38 in.	0.91 in.	5	20	0.05 lbs.	
Z6-5D	1.44 in.	1.38 in.	1.57 in.	5	10	0.06 lbs.	yes
Z6-6	1.12 in.	0.91 in.	1.69 in.	6	15	0.06 lbs.	
Z6-6D	1.3 in.	0.91 in.	2.09 in.	6	10	0.07 lbs.	yes
Z6-10	1.12 in.	1.38 in.	1.69 in.	10	10	0.09 lbs.	
Z6-10D	1.3 in.	1.38 in.	2.09 in.	10	15	0.1 lbs.	yes

Z6 Cable type: flexible copper, Minimum section: 13 AWG, Maximum section: 13 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z6-3	1.08 in.	0.91 in.	0.91 in.	3	30	0.03 lbs.	
Z6-3D	1.44 in.	0.91 in.	1.57 in.	3	10	0.04 lbs.	yes
Z6-5	1.08 in.	1.38 in.	0.91 in.	5	20	0.05 lbs.	
Z6-5D	1.44 in.	1.38 in.	1.57 in.	5	10	0.06 lbs.	yes
Z6-6	1.12 in.	0.91 in.	1.69 in.	6	15	0.06 lbs.	
Z6-6D	1.3 in.	0.91 in.	2.09 in.	6	10	0.07 lbs.	yes
Z6-10	1.12 in.	1.38 in.	1.69 in.	10	10	0.09 lbs.	
Z6-10D	1.3 in.	1.38 in.	2.09 in.	10	15	0.1 lbs.	yes

Z6 Cable type: flexible copper, Minimum section: 11 AWG, Maximum section: 11 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z6-3	1.08 in.	0.91 in.	0.91 in.	3	30	0.03 lbs.	
Z6-3D	1.44 in.	0.91 in.	1.57 in.	3	10	0.04 lbs.	yes
Z6-5	1.08 in.	1.38 in.	0.91 in.	5	20	0.05 lbs.	
Z6-5D	1.44 in.	1.38 in.	1.57 in.	5	10	0.06 lbs.	yes
Z6-6	1.12 in.	0.91 in.	1.69 in.	6	15	0.06 lbs.	
Z6-6D	1.3 in.	0.91 in.	2.09 in.	6	10	0.07 lbs.	yes
Z6-10	1.12 in.	1.38 in.	1.69 in.	10	10	0.09 lbs.	
Z6-10D	1.3 in.	1.38 in.	2.09 in.	10	15	0.1 lbs.	yes

Z6 Cable type: copper, Minimum section: 11 AWG, Maximum section: 11 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z6-3	1.08 in.	0.91 in.	0.91 in.	3	30	0.03 lbs.	
Z6-3D	1.44 in.	0.91 in.	1.57 in.	3	10	0.04 lbs.	yes
Z6-5	1.08 in.	1.38 in.	0.91 in.	5	20	0.05 lbs.	
Z6-5D	1.44 in.	1.38 in.	1.57 in.	5	10	0.06 lbs.	yes
Z6-6	1.12 in.	0.91 in.	1.69 in.	6	15	0.06 lbs.	
Z6-6D	1.3 in.	0.91 in.	2.09 in.	6	10	0.07 lbs.	yes
Z6-10	1.12 in.	1.38 in.	1.69 in.	10	10	0.09 lbs.	
Z6-10D	1.3 in.	1.38 in.	2.09 in.	10	15	0.1 lbs.	yes

Z6 Cable type: flexible copper, Minimum section: 10 AWG, Maximum section: 10 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z6-3	1.08 in.	0.91 in.	0.91 in.	3	30	0.03 lbs.	
Z6-3D	1.44 in.	0.91 in.	1.57 in.	3	10	0.04 lbs.	yes
Z6-5	1.08 in.	1.38 in.	0.91 in.	5	20	0.05 lbs.	
Z6-5D	1.44 in.	1.38 in.	1.57 in.	5	10	0.06 lbs.	yes
Z6-6	1.12 in.	0.91 in.	1.69 in.	6	15	0.06 lbs.	
Z6-6D	1.3 in.	0.91 in.	2.09 in.	6	10	0.07 lbs.	yes
Z6-10	1.12 in.	1.38 in.	1.69 in.	10	10	0.09 lbs.	
Z6-10D	1.3 in.	1.38 in.	2.09 in.	10	15	0.1 lbs.	yes

Z6 Cable type: copper, Minimum section: 10 AWG, Maximum section: 10 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z6-3	1.08 in.	0.91 in.	0.91 in.	3	30	0.03 lbs.	
Z6-3D	1.44 in.	0.91 in.	1.57 in.	3	10	0.04 lbs.	yes
Z6-5	1.08 in.	1.38 in.	0.91 in.	5	20	0.05 lbs.	
Z6-5D	1.44 in.	1.38 in.	1.57 in.	5	10	0.06 lbs.	yes
Z6-6	1.12 in.	0.91 in.	1.69 in.	6	15	0.06 lbs.	
Z6-6D	1.3 in.	0.91 in.	2.09 in.	6	10	0.07 lbs.	yes
Z6-10	1.12 in.	1.38 in.	1.69 in.	10	10	0.09 lbs.	
Z6-10D	1.3 in.	1.38 in.	2.09 in.	10	15	0.1 lbs.	yes