

SINGLE POLE TERMINAL BLOCKS Z16

*indirect clamping
nominal section 6 AWG*

3, 4, 5, 8 and 12 way, single pole terminal blocks. Ideal for use as an equipotential bonding connector for both industrial and domestic use.



CERTIFICATES 



CEI EN 60998-1



CEI 23-21



EN 60998-1



EN 60998-2-1

SINGLE POLE TERMINAL BLOCKS **Z16**

Technical characteristics

Easy entry	yes
UL94 class	V0
IP protection	20
Halogen Free	yes
Impulse voltage	450 V
Max application temperature	185 °F
Material (Body)	Polycarbonate
Material (Clamps)	Electroplated galvanized steel
Material (Connection plate)	ETP Copper electrolytically tinned



SINGLE POLE TERMINAL BLOCKS Z16

List of products

Z16 Cable type: copper, Minimum section: 17 AWG, Maximum section: 17 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z16-8	1.44 in.	1.4 in.	1.97 in.	8	15	0.11 lbs.	
Z16-8D	1.65 in.	1.4 in.	2.24 in.	8	10	0.12 lbs.	yes

Z16 Cable type: flexible copper, Minimum section: 17 AWG, Maximum section: 17 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z16-8	1.44 in.	1.4 in.	1.97 in.	8	15	0.11 lbs.	
Z16-8D	1.65 in.	1.4 in.	2.24 in.	8	10	0.12 lbs.	yes
Z16-12	1.44 in.	4.11 in.	1.28 in.	12	8	0.25 lbs.	
Z16-12D	1.65 in.	4.11 in.	1.97 in.	12	5	0.28 lbs.	yes

Z16 Cable type: flexible copper, Minimum section: 15 AWG, Maximum section: 15 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z16-3	1.5 in.	1.5 in.	1.23 in.	3	20	0.11 lbs.	
Z16-3D	1.73 in.	1.5 in.	1.97 in.	3	15	0.12 lbs.	yes
Z16-4	1.46 in.	1.06 in.	2.13 in.	4	15	0.11 lbs.	
Z16-4D	1.69 in.	1.06 in.	2.28 in.	4	10	0.12 lbs.	yes
Z16-5N	1.5 in.	2.4 in.	1.24 in.	5	10	0.14 lbs.	
Z16-5ND	1.73 in.	2.4 in.	1.97 in.	5	4	0.15 lbs.	yes
Z16-8	1.44 in.	1.4 in.	1.97 in.	8	15	0.11 lbs.	
Z16-8D	1.65 in.	1.4 in.	2.24 in.	8	10	0.12 lbs.	yes
Z16-12	1.44 in.	4.11 in.	1.28 in.	12	8	0.25 lbs.	
Z16-12D	1.65 in.	4.11 in.	1.97 in.	12	5	0.28 lbs.	yes

Z16 Cable type: copper, Minimum section: 15 AWG, Maximum section: 15 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z16-3	1.5 in.	1.5 in.	1.23 in.	3	20	0.11 lbs.	
Z16-3D	1.73 in.	1.5 in.	1.97 in.	3	15	0.12 lbs.	yes
Z16-5N	1.5 in.	2.4 in.	1.24 in.	5	10	0.14 lbs.	
Z16-5ND	1.73 in.	2.4 in.	1.97 in.	5	4	0.15 lbs.	yes
Z16-8	1.44 in.	1.4 in.	1.97 in.	8	15	0.11 lbs.	
Z16-8D	1.65 in.	1.4 in.	2.24 in.	8	10	0.12 lbs.	yes

Z16 Cable type: copper, Minimum section: 13 AWG, Maximum section: 13 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z16-3	1.5 in.	1.5 in.	1.23 in.	3	20	0.11 lbs.	
Z16-3D	1.73 in.	1.5 in.	1.97 in.	3	15	0.12 lbs.	yes
Z16-5N	1.5 in.	2.4 in.	1.24 in.	5	10	0.14 lbs.	
Z16-5ND	1.73 in.	2.4 in.	1.97 in.	5	4	0.15 lbs.	yes
Z16-8	1.44 in.	1.4 in.	1.97 in.	8	15	0.11 lbs.	
Z16-8D	1.65 in.	1.4 in.	2.24 in.	8	10	0.12 lbs.	yes

Z16 Cable type: flexible copper, Minimum section: 13 AWG, Maximum section: 13 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z16-3	1.5 in.	1.5 in.	1.23 in.	3	20	0.11 lbs.	
Z16-3D	1.73 in.	1.5 in.	1.97 in.	3	15	0.12 lbs.	yes
Z16-4	1.46 in.	1.06 in.	2.13 in.	4	15	0.11 lbs.	
Z16-4D	1.69 in.	1.06 in.	2.28 in.	4	10	0.12 lbs.	yes
Z16-5N	1.5 in.	2.4 in.	1.24 in.	5	10	0.14 lbs.	
Z16-5ND	1.73 in.	2.4 in.	1.97 in.	5	4	0.15 lbs.	yes
Z16-8	1.44 in.	1.4 in.	1.97 in.	8	15	0.11 lbs.	
Z16-8D	1.65 in.	1.4 in.	2.24 in.	8	10	0.12 lbs.	yes
Z16-12	1.44 in.	4.11 in.	1.28 in.	12	8	0.25 lbs.	
Z16-12D	1.65 in.	4.11 in.	1.97 in.	12	5	0.28 lbs.	yes

Z16 Cable type: flexible copper, Minimum section: 11 AWG, Maximum section: 11 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z16-3	1.5 in.	1.5 in.	1.23 in.	3	20	0.11 lbs.	
Z16-3D	1.73 in.	1.5 in.	1.97 in.	3	15	0.12 lbs.	yes
Z16-4	1.46 in.	1.06 in.	2.13 in.	4	15	0.11 lbs.	
Z16-4D	1.69 in.	1.06 in.	2.28 in.	4	10	0.12 lbs.	yes
Z16-5N	1.5 in.	2.4 in.	1.24 in.	5	10	0.14 lbs.	
Z16-5ND	1.73 in.	2.4 in.	1.97 in.	5	4	0.15 lbs.	yes
Z16-8	1.44 in.	1.4 in.	1.97 in.	8	15	0.11 lbs.	
Z16-8D	1.65 in.	1.4 in.	2.24 in.	8	10	0.12 lbs.	yes
Z16-12	1.44 in.	4.11 in.	1.28 in.	12	8	0.25 lbs.	
Z16-12D	1.65 in.	4.11 in.	1.97 in.	12	5	0.28 lbs.	yes

Z16 Cable type: copper, Minimum section: 11 AWG, Maximum section: 11 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z16-3	1.5 in.	1.5 in.	1.23 in.	3	20	0.11 lbs.	
Z16-3D	1.73 in.	1.5 in.	1.97 in.	3	15	0.12 lbs.	yes
Z16-5N	1.5 in.	2.4 in.	1.24 in.	5	10	0.14 lbs.	
Z16-5ND	1.73 in.	2.4 in.	1.97 in.	5	4	0.15 lbs.	yes
Z16-8	1.44 in.	1.4 in.	1.97 in.	8	15	0.11 lbs.	
Z16-8D	1.65 in.	1.4 in.	2.24 in.	8	10	0.12 lbs.	yes

Z16 Cable type: flexible copper, Minimum section: 10 AWG, Maximum section: 10 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z16-3	1.5 in.	1.5 in.	1.23 in.	3	20	0.11 lbs.	
Z16-3D	1.73 in.	1.5 in.	1.97 in.	3	15	0.12 lbs.	yes
Z16-4	1.46 in.	1.06 in.	2.13 in.	4	15	0.11 lbs.	
Z16-4D	1.69 in.	1.06 in.	2.28 in.	4	10	0.12 lbs.	yes
Z16-5N	1.5 in.	2.4 in.	1.24 in.	5	10	0.14 lbs.	
Z16-5ND	1.73 in.	2.4 in.	1.97 in.	5	4	0.15 lbs.	yes
Z16-8	1.44 in.	1.4 in.	1.97 in.	8	15	0.11 lbs.	
Z16-8D	1.65 in.	1.4 in.	2.24 in.	8	10	0.12 lbs.	yes
Z16-12	1.44 in.	4.11 in.	1.28 in.	12	8	0.25 lbs.	
Z16-12D	1.65 in.	4.11 in.	1.97 in.	12	5	0.28 lbs.	yes

Z16 Cable type: copper, Minimum section: 10 AWG, Maximum section: 10 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z16-3	1.5 in.	1.5 in.	1.23 in.	3	20	0.11 lbs.	
Z16-3D	1.73 in.	1.5 in.	1.97 in.	3	15	0.12 lbs.	yes
Z16-5N	1.5 in.	2.4 in.	1.24 in.	5	10	0.14 lbs.	
Z16-5ND	1.73 in.	2.4 in.	1.97 in.	5	4	0.15 lbs.	yes
Z16-8	1.44 in.	1.4 in.	1.97 in.	8	15	0.11 lbs.	
Z16-8D	1.65 in.	1.4 in.	2.24 in.	8	10	0.12 lbs.	yes

Z16 Cable type: copper, Minimum section: 7 AWG, Maximum section: 7 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z16-3	1.5 in.	1.5 in.	1.23 in.	3	20	0.11 lbs.	
Z16-3D	1.73 in.	1.5 in.	1.97 in.	3	15	0.12 lbs.	yes
Z16-5ND	1.73 in.	2.4 in.	1.97 in.	5	4	0.15 lbs.	yes
Z16-8	1.44 in.	1.4 in.	1.97 in.	8	15	0.11 lbs.	
Z16-8D	1.65 in.	1.4 in.	2.24 in.	8	10	0.12 lbs.	yes

Z16 Cable type: flexible copper, Minimum section: 7 AWG, Maximum section: 7 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z16-3	1.5 in.	1.5 in.	1.23 in.	3	20	0.11 lbs.	
Z16-3D	1.73 in.	1.5 in.	1.97 in.	3	15	0.12 lbs.	yes
Z16-4	1.46 in.	1.06 in.	2.13 in.	4	15	0.11 lbs.	
Z16-4D	1.69 in.	1.06 in.	2.28 in.	4	10	0.12 lbs.	yes
Z16-5N	1.5 in.	2.4 in.	1.24 in.	5	10	0.14 lbs.	
Z16-5ND	1.73 in.	2.4 in.	1.97 in.	5	4	0.15 lbs.	yes
Z16-8	1.44 in.	1.4 in.	1.97 in.	8	15	0.11 lbs.	
Z16-8D	1.65 in.	1.4 in.	2.24 in.	8	10	0.12 lbs.	yes
Z16-12	1.44 in.	4.11 in.	1.28 in.	12	8	0.25 lbs.	
Z16-12D	1.65 in.	4.11 in.	1.97 in.	12	5	0.28 lbs.	yes

Z16 Cable type: copper, Minimum section: 5 AWG, Maximum section: 5 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z16-3	1.5 in.	1.5 in.	1.23 in.	3	20	0.11 lbs.	
Z16-3D	1.73 in.	1.5 in.	1.97 in.	3	15	0.12 lbs.	yes
Z16-5N	1.5 in.	2.4 in.	1.24 in.	5	10	0.14 lbs.	
Z16-5ND	1.73 in.	2.4 in.	1.97 in.	5	4	0.15 lbs.	yes
Z16-8	1.44 in.	1.4 in.	1.97 in.	8	15	0.11 lbs.	
Z16-8D	1.65 in.	1.4 in.	2.24 in.	8	10	0.12 lbs.	yes

Z16 Cable type: flexible copper, Minimum section: 5 AWG, Maximum section: 5 AWG

Type	Height	Width	Length	Number the hole	Pack qty	Weight	Clamp for DIN
Z16-3	1.5 in.	1.5 in.	1.23 in.	3	20	0.11 lbs.	
Z16-3D	1.73 in.	1.5 in.	1.97 in.	3	15	0.12 lbs.	yes
Z16-4	1.46 in.	1.06 in.	2.13 in.	4	15	0.11 lbs.	
Z16-4D	1.69 in.	1.06 in.	2.28 in.	4	10	0.12 lbs.	yes
Z16-5N	1.5 in.	2.4 in.	1.24 in.	5	10	0.14 lbs.	
Z16-5ND	1.73 in.	2.4 in.	1.97 in.	5	4	0.15 lbs.	yes
Z16-8	1.44 in.	1.4 in.	1.97 in.	8	15	0.11 lbs.	
Z16-8D	1.65 in.	1.4 in.	2.24 in.	8	10	0.12 lbs.	yes
Z16-12	1.44 in.	4.11 in.	1.28 in.	12	8	0.25 lbs.	
Z16-12D	1.65 in.	4.11 in.	1.97 in.	12	5	0.28 lbs.	yes