



MAXIBLOCK CABLE GLANDS 1900 PG

Standard, Pg thread

Cable glands and accessories for control panels and engineering applications.




CERTIFICATES 

 UL 514B  UL 514B

MAXIBLOCK CABLE GLANDS 1900 PG

Technical characteristics

IP protection	IP68
UL94 class	V2
Max operating temperature range (surge)	248 °F
Min operating temperature range (surge)	-4 °F
Max operating temperature range	194 °F
Min operating temperature range	-4 °F
Material (Body)	Polyamide PA6.6
Material (Sealing ring)	Neoprene®



MAXIBLOCK CABLE GLANDS 1900 PG

List of products

1900 Pg										
										
Type	P	Fixing hole diameter	ØA Min	ØA Max	B	C	L Min	L Max	Color	Pack qty
1900DP.09	Pg9	0.61 in.	0.2 in.	0.31 in.	0.75 in.	0.31 in.	0.87 in.	1.02 in.	Grey RAL 7035	100
1900.07	Pg7	0.5 in.	0.14 in.	0.28 in.	0.59 in.	0.31 in.	0.71 in.	0.87 in.	Grey RAL 7035	100
1900.09	Pg9	0.61 in.	0.2 in.	0.31 in.	0.75 in.	0.31 in.	0.87 in.	1.02 in.	Grey RAL 7035	100
1900.11	Pg11	0.74 in.	0.2 in.	0.39 in.	0.87 in.	0.31 in.	0.91 in.	1.1 in.	Grey RAL 7035	100
1900.13	Pg13,5	0.81 in.	0.28 in.	0.47 in.	0.94 in.	0.35 in.	0.94 in.	1.14 in.	Grey RAL 7035	100
1900.16	Pg16	0.89 in.	0.39 in.	0.55 in.	1.06 in.	0.39 in.	1.02 in.	1.22 in.	Grey RAL 7035	50
1900.21	Pg21	1.12 in.	0.51 in.	0.71 in.	1.3 in.	0.47 in.	1.18 in.	1.38 in.	Grey RAL 7035	50
1900.29	Pg29	1.46 in.	0.71 in.	0.98 in.	1.65 in.	0.47 in.	1.3 in.	1.54 in.	Grey RAL 7035	25
1900.36	Pg36	1.86 in.	0.79 in.	1.26 in.	2.09 in.	0.55 in.	1.65 in.	1.93 in.	Grey RAL 7035	10
1900.42	Pg42	2.13 in.	1.1 in.	1.5 in.	2.36 in.	0.55 in.	1.65 in.	1.97 in.	Grey RAL 7035	5
1900.48	Pg48	2.36 in.	1.46 in.	1.77 in.	2.6 in.	0.59 in.	1.77 in.	2.17 in.	Grey RAL 7035	5
1900.07N	Pg7	0.5 in.	0.14 in.	0.28 in.	0.59 in.	0.31 in.	0.71 in.	0.87 in.	Black RAL 9005	100
1900.09N	Pg9	0.61 in.	0.2 in.	0.31 in.	0.75 in.	0.31 in.	0.87 in.	1.02 in.	Black RAL 9005	100
1900.11N	Pg11	0.74 in.	0.2 in.	0.39 in.	0.87 in.	0.31 in.	0.91 in.	1.1 in.	Black RAL 9005	100
1900.13N	Pg13,5	0.81 in.	0.28 in.	0.47 in.	0.94 in.	0.35 in.	0.94 in.	1.14 in.	Black RAL 9005	100
1900.16N	Pg16	0.89 in.	0.39 in.	0.55 in.	1.06 in.	0.39 in.	1.02 in.	1.22 in.	Black RAL 9005	50

1900.21N	Pg21	1.12 in.	0.51 in.	0.71 in.	1.3 in.	0.47 in.	1.18 in.	1.38 in.	Black RAL 9005	50
1900.29N	Pg29	1.46 in.	0.71 in.	0.98 in.	1.65 in.	0.47 in.	1.3 in.	1.54 in.	Black RAL 9005	25
1900.36N	Pg36	1.86 in.	0.79 in.	1.26 in.	2.09 in.	0.55 in.	1.65 in.	1.93 in.	Black RAL 9005	10
1900.42N	Pg42	2.13 in.	1.1 in.	1.5 in.	2.36 in.	0.55 in.	1.65 in.	1.97 in.	Black RAL 9005	5
1900.48N	Pg48	2.36 in.	1.46 in.	1.77 in.	2.6 in.	0.59 in.	1.77 in.	2.17 in.	Black RAL 9005	5
1900.07G	Pg7	0.5 in.	0.14 in.	0.28 in.	0.59 in.	0.31 in.	0.71 in.	0.87 in.	Dark Grey RAL 7001	100
1900.09G	Pg9	0.61 in.	0.2 in.	0.31 in.	0.75 in.	0.31 in.	0.87 in.	1.02 in.	Dark Grey RAL 7001	100
1900.11G	Pg11	0.74 in.	0.2 in.	0.39 in.	0.87 in.	0.31 in.	0.91 in.	1.1 in.	Dark Grey RAL 7001	100
1900.13G	Pg13,5	0.81 in.	0.28 in.	0.47 in.	0.94 in.	0.35 in.	0.94 in.	1.14 in.	Dark Grey RAL 7001	100
1900.16G	Pg16	0.89 in.	0.39 in.	0.55 in.	1.06 in.	0.39 in.	1.02 in.	1.22 in.	Dark Grey RAL 7001	50
1900.21G	Pg21	1.12 in.	0.51 in.	0.71 in.	1.3 in.	0.47 in.	1.18 in.	1.38 in.	Dark Grey RAL 7001	50
1900.29G	Pg29	1.46 in.	0.71 in.	0.98 in.	1.65 in.	0.47 in.	1.3 in.	1.54 in.	Dark Grey RAL 7001	25
1900.36G	Pg36	1.86 in.	0.79 in.	1.26 in.	2.09 in.	0.55 in.	1.65 in.	1.93 in.	Dark Grey RAL 7001	10
1900.42G	Pg42	2.13 in.	1.1 in.	1.5 in.	2.36 in.	0.55 in.	1.65 in.	1.97 in.	Dark Grey RAL 7001	5
1900.48G	Pg48	2.36 in.	1.46 in.	1.77 in.	2.6 in.	0.59 in.	1.77 in.	2.17 in.	Dark Grey RAL 7001	5