

MAXIBLOCK CABLE GLANDS 1910 PG

Reduced cable entry, Pg thread


Cable glands and accessories for control panels and engineering applications.



MAXIBLOCK CABLE GLANDS 1910 PG

Technical characteristics

IP protection	IP68
UL94 class	V2
Max operating temperature range (surge)	248 °F
Min operating temperature range (surge)	-4 °F
Max operating temperature range	194 °F
Min operating temperature range	-4 °F
Material (Body)	Polyamide PA6.6
Material (Sealing ring)	Neoprene®



MAXIBLOCK CABLE GLANDS 1910 PG

List of products

1910 Pg



Type	P	Fixing hole diameter	ØA Min	ØA Max	B	C	L Min	L Max	Color	Pack qty
1910.07	Pg7	0.5 in.	0.08 in.	0.2 in.	0.59 in.	0.31 in.	0.71 in.	0.87 in.	Grey RAL 7035	100
1910.09	Pg9	0.61 in.	0.08 in.	0.24 in.	0.75 in.	0.31 in.	0.87 in.	1.02 in.	Grey RAL 7035	100
1910.11	Pg11	0.74 in.	0.16 in.	0.28 in.	0.87 in.	0.31 in.	0.91 in.	1.1 in.	Grey RAL 7035	100
1910.13	Pg13,5	0.81 in.	0.2 in.	0.39 in.	0.94 in.	0.35 in.	0.94 in.	1.14 in.	Grey RAL 7035	100
1910.16	Pg16	0.89 in.	0.24 in.	0.47 in.	1.06 in.	0.39 in.	1.02 in.	1.22 in.	Grey RAL 7035	50
1910.21	Pg21	1.12 in.	0.35 in.	0.59 in.	1.3 in.	0.47 in.	1.18 in.	1.38 in.	Grey RAL 7035	50
1910.29	Pg29	1.46 in.	0.47 in.	0.79 in.	1.65 in.	0.47 in.	1.3 in.	1.54 in.	Grey RAL 7035	25
1910.36	Pg36	1.86 in.	0.71 in.	1.02 in.	2.09 in.	0.55 in.	1.65 in.	1.93 in.	Grey RAL 7035	10
1910.42	Pg42	2.13 in.	0.98 in.	1.22 in.	2.36 in.	0.55 in.	1.65 in.	1.97 in.	Grey RAL 7035	5
1910.48	Pg48	2.36 in.	1.06 in.	1.54 in.	2.6 in.	0.59 in.	1.77 in.	2.17 in.	Grey RAL 7035	5
1910.07N	Pg7	0.5 in.	0.08 in.	0.2 in.	0.59 in.	0.31 in.	0.71 in.	0.87 in.	Black RAL 9005	100
1910.09N	Pg9	0.61 in.	0.08 in.	0.24 in.	0.75 in.	0.31 in.	0.87 in.	1.02 in.	Black RAL 9005	100
1910.11N	Pg11	0.74 in.	0.16 in.	0.28 in.	0.87 in.	0.31 in.	0.91 in.	1.1 in.	Black RAL 9005	100
1910.13N	Pg13,5	0.81 in.	0.2 in.	0.39 in.	0.94 in.	0.35 in.	0.94 in.	1.14 in.	Black RAL 9005	100
1910.16N	Pg16	0.89 in.	0.24 in.	0.47 in.	1.06 in.	0.39 in.	1.02 in.	1.22 in.	Black RAL 9005	50
1910.21N	Pg21	1.12 in.	0.35 in.	0.59 in.	1.3 in.	0.47 in.	1.18 in.	1.38 in.	Black RAL 9005	50

1910.29N	Pg29	1.46 in.	0.47 in.	0.79 in.	1.65 in.	0.47 in.	1.3 in.	1.54 in.	Black RAL 9005	25
1910.36N	Pg36	1.86 in.	0.71 in.	1.02 in.	2.09 in.	0.55 in.	1.65 in.	1.93 in.	Black RAL 9005	10
1910.42N	Pg42	2.13 in.	0.98 in.	1.22 in.	2.36 in.	0.55 in.	1.65 in.	1.97 in.	Black RAL 9005	5
1910.48N	Pg48	2.36 in.	1.06 in.	1.54 in.	2.6 in.	0.59 in.	1.77 in.	2.17 in.	Black RAL 9005	5