



MAXIBLOCK CABLE GLANDS 1901 PG

Extended thread, Pg thread

Cable glands and accessories for control panels and engineering applications.




CERTIFICATES 

 UL 514B  UL 514B

MAXIBLOCK CABLE GLANDS 1901 PG

Technical characteristics


IP protection	IP68
UL94 class	V2
Max operating temperature range (surge)	248 °F
Min operating temperature range (surge)	-4 °F
Max operating temperature range	194 °F
Min operating temperature range	-4 °F
Material (Body)	Polyamide PA6.6
Material (Sealing ring)	Neoprene®



MAXIBLOCK CABLE GLANDS 1901 PG

List of products

1901 Pg



Type	P	Fixing hole diameter	ØA Min	ØA Max	B	C	L Min	L Max	Color	Pack qty
1901.07	Pg7	0.5 in.	0.14 in.	0.28 in.	0.59 in.	0.59 in.	0.71 in.	0.87 in.	Grey RAL 7035	100
1901.09	Pg9	0.61 in.	0.2 in.	0.31 in.	0.75 in.	0.59 in.	0.87 in.	1.02 in.	Grey RAL 7035	100
1901.11	Pg11	0.74 in.	0.2 in.	0.39 in.	0.87 in.	0.59 in.	0.91 in.	1.1 in.	Grey RAL 7035	100
1901.13	Pg13,5	0.81 in.	0.28 in.	0.47 in.	0.94 in.	0.59 in.	0.94 in.	1.14 in.	Grey RAL 7035	100
1901.16	Pg16	0.89 in.	0.39 in.	0.55 in.	1.06 in.	0.59 in.	1.02 in.	1.22 in.	Grey RAL 7035	50
1901.21	Pg21	1.12 in.	0.51 in.	0.71 in.	1.3 in.	0.59 in.	1.18 in.	1.38 in.	Grey RAL 7035	50
1901.29	Pg29	1.46 in.	0.71 in.	0.98 in.	1.65 in.	0.59 in.	1.3 in.	1.54 in.	Grey RAL 7035	25
1901.36	Pg36	1.86 in.	0.79 in.	1.26 in.	2.09 in.	0.71 in.	1.65 in.	1.93 in.	Grey RAL 7035	10
1901.42	Pg42	2.13 in.	1.1 in.	1.5 in.	2.36 in.	0.71 in.	1.65 in.	1.97 in.	Grey RAL 7035	5
1901.48	Pg48	2.36 in.	1.46 in.	1.77 in.	2.6 in.	0.71 in.	1.77 in.	2.17 in.	Grey RAL 7035	5
1901.07N	Pg7	0.5 in.	0.14 in.	0.28 in.	0.59 in.	0.59 in.	0.71 in.	0.87 in.	Black RAL 9005	100
1901.09N	Pg9	0.61 in.	0.2 in.	0.31 in.	0.75 in.	0.59 in.	0.87 in.	1.02 in.	Black RAL 9005	100
1901.11N	Pg11	0.74 in.	0.2 in.	0.39 in.	0.87 in.	0.59 in.	0.91 in.	1.1 in.	Black RAL 9005	100
1901.13N	Pg13,5	0.81 in.	0.28 in.	0.47 in.	0.94 in.	0.59 in.	0.94 in.	1.14 in.	Black RAL 9005	100
1901.16N	Pg16	0.89 in.	0.39 in.	0.55 in.	1.06 in.	0.59 in.	1.02 in.	1.22 in.	Black RAL 9005	50
1901.21N	Pg21	1.12 in.	0.51 in.	0.71 in.	1.3 in.	0.59 in.	1.18 in.	1.38 in.	Black RAL 9005	50

1901.29N	Pg29	1.46 in.	0.71 in.	0.98 in.	1.65 in.	0.59 in.	1.3 in.	1.54 in.	Black RAL 9005	25
1901.36N	Pg36	1.86 in.	0.79 in.	1.26 in.	2.09 in.	0.71 in.	1.65 in.	1.93 in.	Black RAL 9005	10
1901.42N	Pg42	2.13 in.	1.1 in.	1.5 in.	2.36 in.	0.71 in.	1.65 in.	1.97 in.	Black RAL 9005	5
1901.48N	Pg48	2.36 in.	1.46 in.	1.77 in.	2.6 in.	0.71 in.	1.77 in.	2.17 in.	Black RAL 9005	5