

MAXIBLOCK CABLE GLANDS 1900/X M

Standard factory fitted with locknuts with collar, metric thread M 1,5 pitch


Cable glands and accessories for control panels and engineering applications.



MAXIBLOCK CABLE GLANDS 1900/X M

Technical characteristics

IP protection	IP68
UL94 class	V2
Max operating temperature range (surge)	248 °F
Min operating temperature range (surge)	-4 °F
Max operating temperature range	194 °F
Min operating temperature range	-4 °F
Material (Body)	Polyamide PA6.6
Material (Sealing ring)	Neoprene®



MAXIBLOCK CABLE GLANDS 1900/X M

List of products

1900/X M



Type	P	Fixing hole diameter	ØA Min	ØA Max	B	C	L Min	L Max	Color	Pack qty	Min. pack qty
1900.M12/X	M12X1,5	0.48 in.	0.14 in.	0.28 in.	0.59 in.	0.31 in.	0.71 in.	0.87 in.	Grey RAL 7035	100	10
1900.M16/X	M16X1,5	0.64 in.	0.2 in.	0.39 in.	0.75 in.	0.31 in.	0.87 in.	1.06 in.	Grey RAL 7035	100	10
1900.M20/X	M20X1,5	0.81 in.	0.28 in.	0.51 in.	0.98 in.	0.35 in.	0.94 in.	1.18 in.	Grey RAL 7035	50	10
1900.M25/X	M25X1,5	1 in.	0.39 in.	0.67 in.	1.18 in.	0.39 in.	1.1 in.	1.54 in.	Grey RAL 7035	30	10
1900.M32/X	M32X1,5	1.28 in.	0.51 in.	0.83 in.	1.42 in.	0.39 in.	1.3 in.	1.73 in.	Grey RAL 7035	20	10
1900.M40/X	M40X1,5	1.59 in.	0.75 in.	1.1 in.	1.81 in.	0.39 in.	1.42 in.	1.77 in.	Grey RAL 7035	10	5
1900.M50/X	M50X1,5	1.99 in.	1.06 in.	1.38 in.	2.17 in.	0.47 in.	1.69 in.	2.05 in.	Grey RAL 7035	10	5
1900.M63/X	M63X1,5	2.52 in.	1.34 in.	1.77 in.	2.6 in.	0.47 in.	1.77 in.	2.17 in.	Grey RAL 7035	5	5