

MAXIBLOCK CABLE GLANDS 1900/X PG

Standard factory fitted with locknuts with collar, metric Pg thread


Cable glands and accessories for control panels and engineering applications.



MAXIBLOCK CABLE GLANDS 1900/X PG

Technical characteristics

IP protection	IP68
UL94 class	V2
Max operating temperature range (surge)	248 °F
Min operating temperature range (surge)	-4 °F
Max operating temperature range	194 °F
Min operating temperature range	-4 °F
Material (Body)	Polyamide PA6.6
Material (Sealing ring)	Neoprene®



MAXIBLOCK CABLE GLANDS 1900/X PG

List of products

1900/X Pg



Type	P	Fixing hole diameter	ØA Min	ØA Max	B	C	L Min	L Max	Color	Pack qty	Min. pack qty
1900.07/X	Pg7	0.5 in.	0.14 in.	0.28 in.	0.59 in.	0.31 in.	0.71 in.	0.87 in.	Grey RAL 7035	100	10
1900.09/X	Pg9	0.61 in.	0.2 in.	0.31 in.	0.75 in.	0.31 in.	0.87 in.	1.02 in.	Grey RAL 7035	100	10
1900.11/X	Pg11	0.74 in.	0.2 in.	0.39 in.	0.87 in.	0.31 in.	0.91 in.	1.1 in.	Grey RAL 7035	50	10
1900.13/X	Pg13,5	0.81 in.	0.28 in.	0.47 in.	0.94 in.	0.35 in.	0.94 in.	1.14 in.	Grey RAL 7035	50	10
1900.16/X	Pg16	0.89 in.	0.39 in.	0.55 in.	1.06 in.	0.39 in.	1.02 in.	1.22 in.	Grey RAL 7035	30	10
1900.21/X	Pg21	1.12 in.	0.51 in.	0.71 in.	1.3 in.	0.47 in.	1.18 in.	1.38 in.	Grey RAL 7035	20	10
1900.29/X	Pg29	1.46 in.	0.71 in.	0.98 in.	1.65 in.	0.47 in.	1.3 in.	1.54 in.	Grey RAL 7035	20	10
1900.36/X	Pg36	1.86 in.	0.79 in.	1.26 in.	2.09 in.	0.55 in.	1.65 in.	1.93 in.	Grey RAL 7035	10	5
1900.42/X	Pg42	2.13 in.	1.1 in.	1.5 in.	2.36 in.	0.55 in.	1.65 in.	1.97 in.	Grey RAL 7035	5	5
1900.48/X	Pg48	2.36 in.	1.46 in.	1.77 in.	2.6 in.	0.59 in.	1.77 in.	2.17 in.	Grey RAL 7035	5	5