



# MAXIBLOCK CABLE GLANDS 1900 GAS

*Standard, BSP thread*

Cable glands and accessories for control panels and engineering applications.




CERTIFICATES 

 UL 514B  UL 514B

# MAXIBLOCK CABLE GLANDS 1900 GAS

## *Technical characteristics*


IP protection	IP68
UL94 class	V2
Max operating temperature range (surge)	248 °F
Min operating temperature range (surge)	-4 °F
Max operating temperature range	194 °F
Min operating temperature range	-4 °F
Material (Body)	Polyamide PA6.6
Material (Sealing ring)	Neoprene®



# MAXIBLOCK CABLE GLANDS 1900 GAS

## List of products

### 1900 GAS



Type	P	Fixing hole diameter	ØA Min	ØA Max	B	L Min	L Max	C	Color	Pack qty
1900.14	G1/4"	0.53 in.	0.12 in.	0.26 in.	0.59 in.	0.71 in.	0.87 in.	0.31 in.	Grey RAL 7035	100
1900.38	G3/8"	0.67 in.	0.16 in.	0.31 in.	0.75 in.	0.87 in.	1.02 in.	0.31 in.	Grey RAL 7035	100
1900.12	G1/2"	0.85 in.	0.28 in.	0.47 in.	0.94 in.	0.94 in.	1.14 in.	0.39 in.	Grey RAL 7035	100
1900.34	G3/4"	1.06 in.	0.51 in.	0.71 in.	1.3 in.	1.18 in.	1.38 in.	0.47 in.	Grey RAL 7035	50
1900.14N	G1/4"	0.53 in.	0.12 in.	0.26 in.	0.59 in.	0.71 in.	0.87 in.	0.31 in.	Black RAL 9005	100
1900.38N	G3/8"	0.67 in.	0.16 in.	0.31 in.	0.75 in.	0.87 in.	1.02 in.	0.31 in.	Black RAL 9005	100
1900.12N	G1/2"	0.85 in.	0.28 in.	0.47 in.	0.94 in.	0.94 in.	1.14 in.	0.39 in.	Black RAL 9005	100
1900.34N	G3/4"	1.06 in.	0.51 in.	0.71 in.	1.3 in.	1.18 in.	1.38 in.	0.47 in.	Black RAL 9005	50