

MAXIBLOCK CABLE GLANDS 4900 PG

Atex, Pg thread



CERTIFICATES 



IMQ 10 ATEX 028X



2014/34/EU

MAXIBLOCK CABLE GLANDS 4900 PG

Technical characteristics

Material (Body)	Polyamide PA6
Material (Sealing ring)	Neoprene®
UL94 class	V2
Max application temperature	167 °F
Min application temperature	-4 °F
IP protection	65



MAXIBLOCK CABLE GLANDS 4900 PG

List of products

4900 Pg										
Type	Thread	Fixing hole diameter	Minimum diameter of clamping	Maximum diameter of clamping	Opening key (for the head)	Thread height	Minimum width of clamping	Maximum width of clamping	Color	Pack qty
4900.07	Pg7	0.5 in.	0.14 in.	0.26 in.	0.59 in.	0.31 in.	0.71 in.	0.87 in.	Grey RAL 7035	100
4900.09	Pg9	0.61 in.	0.26 in.	0.31 in.	0.75 in.	0.31 in.	0.87 in.	1.02 in.	Grey RAL 7035	100
4900.11	Pg11	0.74 in.	0.31 in.	0.39 in.	0.87 in.	0.31 in.	0.91 in.	1.1 in.	Grey RAL 7035	100
4900.13	Pg13,5	0.81 in.	0.35 in.	0.47 in.	0.94 in.	0.35 in.	0.94 in.	1.14 in.	Grey RAL 7035	100
4900.16	Pg16	0.89 in.	0.39 in.	0.55 in.	1.06 in.	0.39 in.	1.02 in.	1.22 in.	Grey RAL 7035	50
4900.21	Pg21	1.12 in.	0.55 in.	0.71 in.	1.3 in.	0.47 in.	1.18 in.	1.38 in.	Grey RAL 7035	50
4900.29	Pg29	1.46 in.	0.71 in.	0.87 in.	1.65 in.	0.47 in.	1.3 in.	1.54 in.	Grey RAL 7035	25
4900.36	Pg36	1.86 in.	0.87 in.	1.26 in.	2.09 in.	0.55 in.	1.65 in.	1.93 in.	Grey RAL 7035	10
4900.42	Pg42	2.13 in.	1.1 in.	1.5 in.	2.36 in.	0.55 in.	1.65 in.	1.97 in.	Grey RAL 7035	5
4900.48	Pg48	2.36 in.	1.5 in.	1.89 in.	2.6 in.	0.59 in.	1.77 in.	2.17 in.	Grey RAL 7035	5