

# MAXIBLOCK CABLE GLANDS 4901 PG

*Atex, Pg thread, extended thread*



CERTIFICATES 



IMQ 10 ATEX 028X




2014/34/EU

# MAXIBLOCK CABLE GLANDS 4901 PG

## *Technical characteristics*

Material (Body)	Polyamide PA6
Material (Sealing ring)	Neoprene®
UL94 class	V2
Max application temperature	167 °F
Min application temperature	-4 °F
IP protection	65



# MAXIBLOCK CABLE GLANDS 4901 PG

## List of products

4901 Pg										
Type	Thread	Fixing hole diameter	Minimum diameter of clamping	Maximum diameter of clamping	Opening key (for the head)	Thread height	Minimum width of clamping	Maximum width of clamping	Color	Pack qty
4901.07	Pg7	0.5 in.	0.14 in.	0.26 in.	0.59 in.	0.59 in.	0.71 in.	0.87 in.	Grey RAL 7035	100
4901.09	Pg9	0.61 in.	0.26 in.	0.31 in.	0.75 in.	0.59 in.	0.87 in.	1.02 in.	Grey RAL 7035	100
4901.11	Pg11	0.74 in.	0.31 in.	0.39 in.	0.87 in.	0.59 in.	0.91 in.	1.1 in.	Grey RAL 7035	100
4901.13	Pg13,5	0.81 in.	0.35 in.	0.47 in.	0.94 in.	0.59 in.	0.94 in.	1.14 in.	Grey RAL 7035	100
4901.16	Pg16	0.89 in.	0.39 in.	0.55 in.	1.06 in.	0.59 in.	1.02 in.	1.22 in.	Grey RAL 7035	50
4901.21	Pg21	1.12 in.	0.55 in.	0.71 in.	1.3 in.	0.59 in.	1.18 in.	1.38 in.	Grey RAL 7035	50
4901.29	Pg29	1.46 in.	0.71 in.	0.87 in.	1.65 in.	0.59 in.	1.3 in.	1.54 in.	Grey RAL 7035	25
4901.36	Pg36	1.86 in.	0.87 in.	1.26 in.	2.09 in.	0.71 in.	1.65 in.	1.93 in.	Grey RAL 7035	10
4901.42	Pg42	2.13 in.	1.1 in.	1.5 in.	2.36 in.	0.71 in.	1.65 in.	1.97 in.	Grey RAL 7035	5
4901.48	Pg48	2.36 in.	1.5 in.	1.77 in.	2.6 in.	0.71 in.	1.77 in.	2.17 in.	Grey RAL 7035	5