

## MAXIBRASS CABLE GLANDS 2910 M

*Reduced cable entry, metric thread M 1,5 pitch*



CERTIFICATES 



UL 514B



UL 514B



EN 62444:2013



EN 62444: 2013

# MAXIBRASS CABLE GLANDS 2910 M

## *Technical characteristics*


Material (Body)	Nickel plated brass
Material (Sealing ring)	Neoprene®
Material (Cable grip insert)	Polyamide PA6.6
Material (O-Ring)	Nitrile 70 sh A
Max operating temperature range	212 °F
Min operating temperature range	-13 °F



## MAXIBRASS CABLE GLANDS 2910 M

### List of products

#### 2910 M



Type	P	Fixing hole diameter	ØA Min	ØA Max	B	E	C	L Min	L Max	Pack qty
2910.M12N	M12X1,5	0.48 in.	0.04 in.	0.2 in.	0.63 in.	0.71 in.	0.26 in.	0.63 in.	0.79 in.	100
2910.M16N	M16X1,5	0.64 in.	0.1 in.	0.28 in.	0.79 in.	0.91 in.	0.28 in.	0.79 in.	0.98 in.	100
2910.M20N	M20X1,5	0.81 in.	0.2 in.	0.39 in.	0.94 in.	1.06 in.	0.31 in.	0.79 in.	1.06 in.	50
2910.M25N	M25X1,5	1 in.	0.24 in.	0.51 in.	1.14 in.	1.26 in.	0.31 in.	0.94 in.	1.18 in.	50
2910.M32N	M32X1,5	1.28 in.	0.28 in.	0.55 in.	1.42 in.	1.57 in.	0.35 in.	1.06 in.	1.34 in.	25
2910.M40N	M40X1,5	1.59 in.	0.51 in.	0.91 in.	1.77 in.	1.97 in.	0.35 in.	1.34 in.	1.65 in.	10
2910.M50N	M50X1,5	1.99 in.	0.79 in.	1.14 in.	2.13 in.	2.36 in.	0.39 in.	1.38 in.	1.69 in.	8
2910.M63N	M63X1,5	2.52 in.	1.06 in.	1.54 in.	2.64 in.	2.91 in.	0.59 in.	1.57 in.	2.05 in.	5