



# MAXIBRASS CABLE GLANDS 2901 PG

*Extended thread, Pg thread*



CERTIFICATES 

 UL 514B  UL 514B

# MAXIBRASS CABLE GLANDS 2901 PG

## *Technical characteristics*

Material (Body)	Nickel plated brass
Material (Sealing ring)	Neoprene®
Material (Cable grip insert)	Polyamide PA6.6
Material (O-Ring)	Nitrile 70 sh A
Max operating temperature range	212 °F
Min operating temperature range	-13 °F



## MAXIBRASS CABLE GLANDS 2901 PG

### *List of products*

<b>2901 Pg</b>										
Type	P	Fixing hole diameter	ØA Min	ØA Max	B	E	C	L Min	L Max	Pack qty
2901.07N	Pg7	0.5 in.	0.12 in.	0.28 in.	0.63 in.	0.71 in.	0.47 in.	0.67 in.	0.79 in.	100
2901.09N	Pg9	0.61 in.	0.16 in.	0.31 in.	0.67 in.	0.75 in.	0.47 in.	0.63 in.	0.91 in.	100
2901.11N	Pg11	0.74 in.	0.18 in.	0.39 in.	0.79 in.	0.91 in.	0.47 in.	0.79 in.	0.98 in.	100
2901.13N	Pg13,5	0.81 in.	0.2 in.	0.47 in.	0.87 in.	0.98 in.	0.47 in.	0.79 in.	1.02 in.	50
2901.16N	Pg16	0.89 in.	0.28 in.	0.51 in.	0.94 in.	1.06 in.	0.47 in.	0.79 in.	1.06 in.	50
2901.21N	Pg21	1.12 in.	0.39 in.	0.67 in.	1.18 in.	1.3 in.	0.47 in.	0.94 in.	1.18 in.	50
2901.29N	Pg29	1.46 in.	0.67 in.	0.98 in.	1.57 in.	1.77 in.	0.59 in.	1.18 in.	1.46 in.	25
2901.36N	Pg36	1.86 in.	0.79 in.	1.26 in.	1.97 in.	2.17 in.	0.59 in.	1.5 in.	1.89 in.	10
2901.42N	Pg42	2.13 in.	1.1 in.	1.5 in.	2.24 in.	2.48 in.	0.59 in.	1.54 in.	1.89 in.	5