



MAXIBRASS CABLE GLANDS 2911 PG

Extended thread and reduced cable entry, Pg thread



CERTIFICATES 

 UL 514B  UL 514B

MAXIBRASS CABLE GLANDS 2911 PG

Technical characteristics

Material (Body)	Nickel plated brass
Material (Sealing ring)	Neoprene®
Material (Cable grip insert)	Polyamide PA6.6
Material (O-Ring)	Nitrile 70 sh A
Max operating temperature range	212 °F
Min operating temperature range	-13 °F



MAXIBRASS CABLE GLANDS 2911 PG

List of products

2911 Pg



Type	P	Fixing hole diameter	ØA Min	ØA Max	B	E	C	L Min	L Max	Pack qty
2911.07N	Pg7	0.5 in.	0.04 in.	0.2 in.	0.63 in.	0.71 in.	0.47 in.	0.63 in.	0.79 in.	100
2911.09N	Pg9	0.61 in.	0.08 in.	0.24 in.	0.67 in.	0.75 in.	0.47 in.	0.67 in.	0.91 in.	100
2911.11N	Pg11	0.74 in.	0.1 in.	0.28 in.	0.79 in.	0.91 in.	0.47 in.	0.79 in.	0.98 in.	100
2911.13N	Pg13,5	0.81 in.	0.16 in.	0.39 in.	0.87 in.	0.98 in.	0.47 in.	0.79 in.	1.02 in.	50
2911.16N	Pg16	0.89 in.	0.2 in.	0.39 in.	0.94 in.	1.06 in.	0.47 in.	0.79 in.	1.06 in.	100
2911.21N	Pg21	1.12 in.	0.24 in.	0.51 in.	1.18 in.	1.3 in.	0.47 in.	0.94 in.	1.18 in.	50
2911.29N	Pg29	1.46 in.	0.43 in.	0.79 in.	1.57 in.	1.77 in.	0.59 in.	1.18 in.	1.46 in.	25
2911.36N	Pg36	1.86 in.	0.71 in.	1.02 in.	1.97 in.	2.17 in.	0.59 in.	1.5 in.	1.89 in.	10
2911.42N	Pg42	2.13 in.	0.94 in.	1.22 in.	2.24 in.	2.48 in.	0.59 in.	1.54 in.	1.89 in.	5