

## MAXIINOX CABLE GLANDS 7900

*Stainless Steel 303 (X8 CrNiS 18-9)*



CERTIFICATES 

 BT 2006/95/CE

# MAXIINOX CABLE GLANDS 7900

## *Technical characteristics*

Material (Body)	Stainless steel AISI 303
Material (Sealing ring)	Neoprene®
Material (Cable grip insert)	Polyamide PA6.6
Material (O-Ring)	Nitrile 70 sh A



# MAXIINOX CABLE GLANDS 7900

## List of products

### 7900 M



Type	P	Fixing hole diameter	ØA Min	ØA Max	B	E	C	L Min	L Max	Pack qty	Min. pack qty
7900.M12	M12X1,5	0.48 in.	0.12 in.	0.28 in.	0.63 in.	0.71 in.	0.26 in.	0.63 in.	0.79 in.	90	30
7900.M16	M16X1,5	0.64 in.	0.18 in.	0.39 in.	0.79 in.	0.91 in.	0.28 in.	0.79 in.	0.98 in.	120	30
7900.M20	M20X1,5	0.81 in.	0.28 in.	0.51 in.	0.94 in.	1.06 in.	0.31 in.	0.79 in.	1.06 in.	75	25
7900.M25	M25X1,5	1 in.	0.39 in.	0.67 in.	1.14 in.	1.26 in.	0.31 in.	0.94 in.	1.18 in.	40	20
7900.M32	M32X1,5	1.28 in.	0.43 in.	0.83 in.	1.42 in.	1.57 in.	0.35 in.	1.06 in.	1.34 in.	15	
7900.M40	M40X1,5	1.59 in.	0.75 in.	1.1 in.	1.77 in.	1.97 in.	0.35 in.	1.34 in.	1.65 in.	15	
7900.M50	M50X1,5	1.99 in.	1.02 in.	1.38 in.	2.13 in.	2.36 in.	0.39 in.	1.38 in.	1.69 in.	10	
7900.M63	M63X1,5	2.52 in.	1.34 in.	1.77 in.	2.64 in.	2.91 in.	0.59 in.	1.57 in.	2.05 in.	5	

**7900 Pg**


Type	P	Fixing hole diameter	ØA Min	ØA Max	B	E	C	L Min	L Max	Pack qty	Min. pack qty
7900.07	Pg7	0.5 in.	0.12 in.	0.28 in.	0.63 in.	0.71 in.	0.2 in.	0.79 in.	0.63 in.	90	30
7900.09	Pg9	0.61 in.	0.16 in.	0.31 in.	0.67 in.	0.75 in.	0.24 in.	0.91 in.	0.67 in.	90	30
7900.11	Pg11	0.74 in.	0.18 in.	0.39 in.	0.79 in.	0.91 in.	0.24 in.	0.98 in.	0.79 in.	60	30
7900.13	Pg13,5	0.81 in.	0.2 in.	0.47 in.	0.87 in.	0.98 in.	0.26 in.	1.02 in.	0.79 in.	90	30
7900.16	Pg16	0.89 in.	0.28 in.	0.51 in.	0.94 in.	1.06 in.	0.26 in.	1.06 in.	0.79 in.	60	30
7900.21	Pg21	1.12 in.	0.39 in.	0.67 in.	1.18 in.	1.3 in.	0.28 in.	1.18 in.	0.94 in.	40	20
7900.29	Pg29	1.46 in.	0.67 in.	0.98 in.	1.57 in.	1.77 in.	0.31 in.	1.46 in.	0.12 in.	30	15
7900.36	Pg36	1.86 in.	0.79 in.	1.26 in.	1.97 in.	2.17 in.	0.31 in.	1.89 in.	1.5 in.	10	
7900.42	Pg42	2.13 in.	1.1 in.	1.5 in.	2.24 in.	2.48 in.	0.39 in.	1.81 in.	1.42 in.	5	
7900.48	Pg48	2.36 in.	1.34 in.	1.77 in.	2.64 in.	2.91 in.	0.59 in.	2.05 in.	1.57 in.	5	