

## MAXIINOX CABLE GLANDS 7900A M

*Metric thread M 1,5 pitch*



## MAXIINOX CABLE GLANDS 7900A M

### *Technical characteristics*

Material (Body)	Stainless steel AISI 316L
Material (Sealing ring)	Neoprene®
Material (Cable grip insert)	Polyamide PA6.6
Material (O-Ring)	Nitrile 70 sh A



# MAXIINOX CABLE GLANDS 7900A M

## List of products

### 7900A M



Type	P	Fixing hole diameter	ØA Min	ØA Max	B	E	C	L Min	L Max	Pack qty	Min. pack qty
7900A.M12	M12X1,5	0.48 in.	0.12 in.	0.28 in.	0.63 in.	0.71 in.	0.26 in.	0.63 in.	0.79 in.	60	20
7900A.M16	M16X1,5	0.64 in.	0.18 in.	0.39 in.	0.79 in.	0.91 in.	0.28 in.	0.79 in.	0.98 in.	80	20
7900A.M20	M20X1,5	0.81 in.	0.28 in.	0.51 in.	0.94 in.	1.06 in.	0.31 in.	0.79 in.	1.06 in.	60	20
7900A.M25	M25X1,5	1 in.	0.39 in.	0.67 in.	1.14 in.	1.26 in.	0.31 in.	0.94 in.	1.18 in.	30	15
7900A.M32	M32X1,5	1.28 in.	0.43 in.	0.83 in.	1.42 in.	1.57 in.	0.35 in.	1.06 in.	1.34 in.	12	
7900A.M40	M40X1,5	1.59 in.	0.75 in.	1.1 in.	1.77 in.	1.97 in.	0.35 in.	1.34 in.	1.65 in.	10	
7900A.M50	M50X1,5	1.99 in.	1.02 in.	1.38 in.	2.13 in.	2.36 in.	0.39 in.	1.38 in.	1.69 in.	7	
7900A.M63	M63X1,5	2.52 in.	1.34 in.	1.77 in.	2.64 in.	2.91 in.	0.59 in.	1.57 in.	2.05 in.	5	