

RUTASEAL GROMMETS RS



RUTASEAL GROMMETS RS

Technical characteristics


Material (Body)	EPDM halogen- free
Color	Dark Grey RAL 7001
IP protection	67
Min operating temperature range	-40 °F
Max operating temperature range	230 °F



RUTASEAL GROMMETS RS

List of products

RS



Type	Thread	A	B	C	D	Pack qty	Min. pack qty
RS0407.M12	M12	0.49 in.	0.02 in.	0.22 in.	0.79 in.	2,000	50
RS0509.M16	M16	0.65 in.	0.04 in.	0.43 in.	0.83 in.	2,000	50
RS0831.M20	M20	0.81 in.	0.04 in.	0.53 in.	1 in.	3,000	50
RS1117.M25	Pg13,5	1 in.	0.04 in.	0.6 in.	1.2 in.	2,000	50
RS1117.M25	Pg13,5	1 in.	0.04 in.	0.6 in.	1.2 in.	2,000	50
RS1520.M32	M32	1.28 in.	0.04 in.	0.73 in.	1.52 in.	1,000	25
RS1928.M40	M40	1.59 in.	0.04 in.	0.85 in.	1.91 in.	600	25
RS2735.M50	M50	1.99 in.	0.04 in.	0.98 in.	2.38 in.	250	10
RS0305.07	Pg7	0.49 in.	0.02 in.	0.21 in.	0.79 in.	2,000	50
RS0507.09	Pg9	0.63 in.	0.04 in.	0.41 in.	0.83 in.	2,000	50
RS0710.11	Pg11	0.75 in.	0.04 in.	0.5 in.	0.94 in.	3,000	50
RS1014.16	Pg16	0.91 in.	0.04 in.	0.58 in.	1.1 in.	2,000	50
RS1420.21	Pg21	1.14 in.	0.04 in.	0.69 in.	1.38 in.	1,000	25
RS2026.29	Pg29	1.5 in.	0.04 in.	0.79 in.	1.81 in.	600	25
RS2635.36	Pg36	1.89 in.	0.04 in.	0.94 in.	2.28 in.	250	10