

SPIRALBLOCK CABLE GLANDS 1500

Polyamide PA6.6



SPIRALBLOCK CABLE GLANDS 1500

Technical characteristics

Material (Body)	Polyamide PA6.6
Material (Sealing ring)	Neoprene®
IP protection	IP68
UL94 class	V2
Max operating temperature range (surge)	248 °F
Min operating temperature range (surge)	-4 °F
Max operating temperature range	194 °F
Min operating temperature range	-4 °F



SPIRALBLOCK CABLE GLANDS 1500

List of products

1500 M

Type	C	Fixing hole diameter	B	ØA Min	ØA Max	P	L Max	Color	Pack qty
1500.M12	M12X1,5	0.48 in.	0.14 in.	0.28 in.	0.59 in.	0.31 in.	2.24 in.	Grey RAL 7035	100
1500.M16	M16X1,5	0.64 in.	0.2 in.	0.39 in.	0.75 in.	0.31 in.	3.11 in.	Grey RAL 7035	50
1500.M25	M25X1,5	1 in.	0.39 in.	0.67 in.	1.18 in.	0.39 in.	4.72 in.	Grey RAL 7035	20
1500.M20	M20X1,5	0.81 in.	0.28 in.	0.51 in.	0.98 in.	0.35 in.	3.54 in.	Grey RAL 7035	25
1500.M32	M32X1,5	1.28 in.	0.51 in.	0.83 in.	1.42 in.	0.39 in.	5.51 in.	Grey RAL 7035	10
1500.M12N	M12X1,5	0.48 in.	0.14 in.	0.28 in.	0.59 in.	0.31 in.	2.24 in.	Black RAL 9005	100
1500.M16N	M16X1,5	0.64 in.	0.2 in.	0.39 in.	0.75 in.	0.31 in.	3.11 in.	Black RAL 9005	50
1500.M20N	M20X1,5	0.81 in.	0.28 in.	0.51 in.	0.98 in.	0.35 in.	3.54 in.	Black RAL 9005	25
1500.M25N	M25X1,5	1 in.	0.39 in.	0.67 in.	1.18 in.	0.39 in.	4.72 in.	Black RAL 9005	20
1500.M32N	M32X1,5	1.28 in.	0.51 in.	0.83 in.	1.42 in.	0.39 in.	5.51 in.	Black RAL 9005	10

1500 Pg

Type	C	Fixing hole diameter	B	ØA Min	ØA Max	P	L Max	Color	Pack qty
1500.07	Pg7	0.5 in.	0.14 in.	0.28 in.	0.59 in.	0.31 in.	2.24 in.	Grey RAL 7035	100
1500.09	Pg9	0.61 in.	0.2 in.	0.31 in.	0.75 in.	0.31 in.	2.68 in.	Grey RAL 7035	100
1500.11	Pg11	0.74 in.	0.2 in.	0.39 in.	0.87 in.	0.31 in.	3.15 in.	Grey RAL 7035	50
1500.13	Pg13,5	0.81 in.	0.28 in.	0.47 in.	0.55 in.	0.39 in.	3.54 in.	Grey RAL 7035	50
1500.16	Pg16	0.89 in.	0.39 in.	0.55 in.	1.06 in.	0.39 in.	3.94 in.	Grey RAL 7035	25
1500.21	Pg21	1.12 in.	0.51 in.	0.71 in.	1.3 in.	0.47 in.	4.41 in.	Grey RAL 7035	20
1500.07N	Pg7	0.5 in.	0.14 in.	0.28 in.	0.59 in.	0.31 in.	2.24 in.	Black RAL 9005	100
1500.09N	Pg9	0.61 in.	0.2 in.	0.31 in.	0.75 in.	0.31 in.	2.68 in.	Black RAL 9005	100
1500.11N	Pg11	0.74 in.	0.2 in.	0.39 in.	0.87 in.	0.31 in.	3.15 in.	Black RAL 9005	50
1500.13N	Pg13,5	0.81 in.	0.28 in.	0.47 in.	0.94 in.	0.39 in.	3.54 in.	Black RAL 9005	50
1500.16N	Pg16	0.89 in.	0.39 in.	0.55 in.	1.06 in.	0.39 in.	3.94 in.	Black RAL 9005	25
1500.21N	Pg21	1.12 in.	0.51 in.	0.71 in.	1.3 in.	0.47 in.	4.41 in.	Black RAL 9005	20

1500 GAS

Type	C	Fixing hole diameter	B	ØA Min	ØA Max	P	L Max	Color	Pack qty
1500.14N	G1/4"	0.53 in.	0.12 in.	0.26 in.	0.59 in.	0.31 in.	2.24 in.	Black RAL 9005	100
1500.38	G3/8"	0.67 in.	0.16 in.	0.31 in.	0.75 in.	0.35 in.	2.68 in.	Grey RAL 7035	100
1500.38N	G3/8"	0.67 in.	0.16 in.	0.31 in.	0.75 in.	0.35 in.	2.68 in.	Black RAL 9005	100
1500.12	G1/2"	0.85 in.	0.28 in.	0.47 in.	0.94 in.	0.39 in.	3.54 in.	Grey RAL 7035	50
1500.12N	G1/2"	0.85 in.	0.28 in.	0.47 in.	0.94 in.	0.39 in.	3.54 in.	Black RAL 9005	50
1500.34	G3/4"	1.06 in.	0.51 in.	0.71 in.	1.3 in.	0.47 in.	4.41 in.	Grey RAL 7035	20
1500.34N	G3/4"	1.06 in.	0.51 in.	0.71 in.	1.3 in.	0.47 in.	4.41 in.	Black RAL 9005	20
1500.14	G1/4"	0.53 in.	0.12 in.	0.26 in.	0.59 in.	0.31 in.	2.24 in.	Grey RAL 7035	100