

SINGLE POLE TERMINAL BLOCKS Z16-3D

*indirect clamping
nominal section 6 AWG*

3, 4, 5, 8 and 12 way, single pole terminal blocks. Ideal for use as an equipotential bonding connector for both industrial and domestic use.



CERTIFICATES 



CEI EN 60998-1



CEI 23-21



EN 60998-1



EN 60998-2-1

SINGLE POLE TERMINAL BLOCKS Z16-3D

Technical characteristics

PROPERTIES

Height	1.73 in.
Width	1.5 in.
Length	1.97 in.
Number the hole	3
Pack qty	15
Weight	0.12 lbs.
Impulse voltage	450 V
Clamp for DIN	yes
Easy entry	yes
UL94 class	V0
IP protection	20
Halogen Free	yes
Impulse voltage	450 V
Max application temperature	185 °F
Material (Body)	Polycarbonate
Material (Clamps)	Electroplated galvanized steel
Material (Connection plate)	ETP Copper electrolytically tinned
Max application temperature	185 °F
UL94 class	V0
IP protection	20
Easy entry	yes
Material (Body)	Polycarbonate
Material (Clamps)	Electroplated galvanized steel
Material (Connection plate)	ETP Copper electrolytically tinned



SINGLE POLE TERMINAL BLOCKS **Z16-3D**