

SINGLE POLE TERMINAL BLOCKS Z35-6D

*indirect clamping
nominal section 2 AWG*

3, 4, 6, and 11 way, single pole terminal blocks.
Ideal for use as an equipotential bonding connector for both
industrial and domestic use.



CERTIFICATES 



CEI EN 60998-1



CEI 23-21



EN 60998-1



EN 60998-2-1

SINGLE POLE TERMINAL BLOCKS Z35-6D

Technical characteristics

PROPERTIES

Height	2.05 in.
Width	3.27 in.
Length	1.93 in.
Number the hole	6
Pack qty	5
Weight	0.31 lbs.
Impulse voltage	450 V
Clamp for DIN	yes
Easy entry	yes
UL94 class	V0
IP protection	20
Halogen Free	yes
Impulse voltage	450 V
Max application temperature	185 °F
Material (Body)	Polycarbonate
Material (Clamps)	Electroplated galvanized steel
Material (Connection plate)	ETP Copper electrolytically tinned
Max application temperature	185 °F
UL94 class	V0
IP protection	20
Easy entry	yes
Material (Body)	Polycarbonate
Material (Clamps)	Electroplated galvanized steel
Material (Connection plate)	ETP Copper electrolytically tinned



SINGLE POLE TERMINAL BLOCKS **Z35-6D**