

## HYDRAULIC PUMPS PO7000

New foot operated double speed pump, developing a maximum pressure of 10,000 psi. The pump is supplied with 10FT long high pressure flexible hose complete with female self-lock quick coupler. Pressure can be withdrawn at any time during operation by depressing the release lever. A solid shaped stand gives the pump stability during operation.



# HYDRAULIC PUMPS PO7000

## *Technical characteristics*

### PROPERTIES

Nominal pressure	10150 psi
Height	6.42 in.
Width	7.87 in.
Length	26.77 in.
Weight	21.56 lbs.



## HYDRAULIC PUMPS PO7000

*In the same kit*

Storage

CASE VAL - Plastic case VAL P21

## Products used together

### Tools

HYDRAULIC CUTTING HEAD TC025 - TC025

HYDRAULIC CUTTING HEAD TC050Y - TC050Y

HYDRAULIC CUTTING HEAD TC065-SC - TC065-SC

HYDRAULIC CUTTING HEAD TC096 - TC096

HYDRAULIC CUTTING HEAD, INDUSTRIAL APPLICATION TC096-KV - TC096-KV

Hydraulic nut splitting tools RHTD

Double blade head RHTD410T      RHTD270

HYDRAULIC PRESSHEAD RHC131LN - RHC131LN

HYDRAULIC PRESSHEAD RHU131-C - RHU131-C

HYDRAULIC PRESSHEADS RH50 - RH50

HYDRAULIC PRESSHEADS RHU520 - RHU520

INSULATED HYDRAULIC PRESSHEAD RHC131LN-KV - RHC131LN-KV

PRESSURE TEST DEVICE FOR HYDRAULIC PUMPS AND TOOLS MPC1 - MPC1

SPECIAL TOOLS

Frame-type hole

punching head

RH-FC48N - RH-FC48N

HYDRAULIC CUTTING HEAD TC050 - TC050

HYDRAULIC CUTTING HEAD TC055 - TC055

HYDRAULIC CUTTING HEAD TC085 - TC085

HYDRAULIC CUTTING HEAD TC120 - TC120

HYDRAULIC CUTTING TOOLS RH-TFC - RH-TFC

HYDRAULIC PRESSHEAD RHC131 - RHC131

HYDRAULIC PRESSHEAD RHM132 - RHM132

HYDRAULIC PRESSHEADS ECW-H3D - ECW-H3D

HYDRAULIC PRESSHEADS RHM50 - RHM50

HYDRAULIC PRESSHEADS RHU600 - RHU600

Piercing heads RHT

RHT160      RHT160-60N

Puller-type hole punching head RH-FL75 - RH-FL75